

## ARCHIVIO ISTITUZIONALE DELLA RICERCA

### Alma Mater Studiorum Università di Bologna Archivio istituzionale della ricerca

Environmental productivity index GIS-based model to estimate prickly pear biomass potential availability for biogas production

This is the final peer-reviewed author's accepted manuscript (postprint) of the following publication:

Published Version:

Leanza P.M., Valenti F., D'Urso P.R., Arcidiacono C. (2022). Environmental productivity index GIS-based model to estimate prickly pear biomass potential availability for biogas production. AGRONOMY JOURNAL, 114(6), 3206-3224 [10.1002/agj2.21192].

Availability:

This version is available at: https://hdl.handle.net/11585/933694 since: 2023-07-05

Published:

DOI: http://doi.org/10.1002/agj2.21192

Terms of use:

Some rights reserved. The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website.

This item was downloaded from IRIS Università di Bologna (https://cris.unibo.it/). When citing, please refer to the published version.

(Article begins on next page)

## This is the final peer-reviewed accepted manuscript of:

Leanza, P. M., Valenti, F., D'Urso, P. R., & Arcidiacono, C. (2022). Environmental productivity index GIS-based model to estimate prickly pear biomass potential availability for biogas production. *Agronomy Journal*, 114, 3206–3224.

## The final published version is available online at:

https://doi.org/10.1002/agj2.21192

#### Terms of use:

Some rights reserved. The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website.

This item was downloaded from IRIS Università di Bologna (<u>https://cris.unibo.it/</u>)

When citing, please refer to the published version.

#### **Core Ideas**

As part of the submission process, we ask authors to prepare highlights of their article. The highlights will consist of 3 to 5 bullet points that convey the core findings of the article and emphasize the novel aspects and impacts of the research on scientific progress and environmental problem solving.

The purpose of these highlights is to give a concise summary that will be helpful in assessing the suitability of the manuscript for publication in the journal and for selecting appropriate reviewers. If the article is accepted the highlights may also be used for promoting and publicizing the research.

Core Idea 1: -	The use of Opuntia ficus indica biomass for anaerobic digestion was assessed
Core Idea 2: -	The methodology was applied by combining models and spatial analysis tools
Core Idea 3: -	The study was carried out from data acquired at local scale to a territorial level
Core Idea 4: -	Based on bioclimatic data, the Environmental Productivity Index was estimated
Core Idea 5: - hectare were co	The most suitable areas for producing biogas and electricity per year and per omputed

#### 1 **EPI GIS- based model to estimate prickly pear biomass potential**

#### 2 availability for biogas production: an application to a Mediterranean area

3	Paola Maria Leanza <sup>a</sup> , Francesca Valenti <sup>a*</sup> , Provvidenza Rita D'Urso <sup>a</sup> , Claudia Arcidiacono <sup>a</sup>
4	
5	<u>paola.leanza@unict.it, francesca.valenti@unict.it, provvidenza.durso@phd.unict.it, carcidi@unict.it</u>
6	
7	a University of Catania, Department of Agriculture, Food and Environment, Building and Land Engineering
8	Section, via S. Sofia 100, 95123, Catania, Italy
9	
10	*Corresponding author: Francesca Valenti, University of Catania, Department of Agriculture, Food and
11	Environment, Building and Land Engineering Section, via S. Sofia 100, 95123, Catania, Italy. email:
12	francesca.valenti@unict.it; phone: +390957147580

#### 13 Abstract

14 Nowadays, climate change is the environmental issue facing the world. To reach the 2030 EU goals, recently, biogas production by anaerobic digestion has developed significantly, by using 15 16 alternative biomass sources due to the competition between food and no-food products. In this 17 regard, Opuntia ficus-indica (OFI) has been suggested as a suitable new biomass for producing 18 biomethane within the context of circular economy. In this study, a predictive methodology was 19 applied by combining the Nobel model of Environmental Productivity Index (EPI) and Geographic 20 Information System (GIS), with the aim of estimating OFI biomass amount, as well as biogas and 21 electricity potential production. 22 GIS analyses allowed the identification of the most suitable territorial areas for producing

23 biogas from *OFI*, and an estimation of electricity production. The achieved results are highly

24 valuable information for strategic planning of biogas sector development and could be relevant to

25 the intervention priorities established by the European Union.

#### 26 Keywords: Opuntia ficus-indica; GIS; spatial analysis, EPI, bioenergy, biomass

#### 27 **1 Introduction**

28 Demand for renewable biomass-based carbon resources to use for lignocellulosic biofuels is 29 expected to increase in the future due to the reduction of GHG released into the atmosphere (Aosaar 30 & Varik, 2012; Yang et al., 2015). Nowadays, the production of biogas by anaerobic digestion has 31 developed significantly, by using alternative biomass sources due to the competition between food 32 and no-food products (Dale et al., 2016). Furthermore, water availability is the crucial factor that 33 limit the cultivation of bioenergy crops, therefore on those water-limited areas the crassulacean acid 34 metabolism (CAM) species such as Agave (Agavaceae) and Opuntia (prickly pear) could be 35 suitable biomasses due to their growth characteristics that allow to thrive in semi-arid regions (Yang et al., 2015). 36

37 Prickly pear is widely used within the food, pharmaceutical and cosmetic, and textile 38 industries (Ortiz-Laurel et al., 2014) but is also recognised as a bioenergetic crop, for production of 39 lignocellulosic biofuels, biogas, and biofertilisers. Crops characterised by a CAM, such as Opuntia ficus-indica (OFI), are a recommended resource for alternative energy production as they have a 40 41 high potential for biomass production (Nobel & de Cortázar;1991; de Cortázar & Nobel, 1992; de 42 Cortázar & Varnero, 1999, Mason et al., 2015). In this regard, it is well known that the chemical composition of the biomass, the degree of solubilisation, and hydrolysis of the organic matter 43 44 within the digester are crucial factors for the anaerobic digestion process in order to obtain a high 45 anaerobic biodegradability and a high biogas yield (Santos et al., 2016; Valenti et al., 2018a). Since 46 it is demonstrated that a large fraction of the stems, also known as cladodes, is biodegradable, this 47 implies that they could constitute an important source of feedstock for biogas production (Jigar et 48 al., 2011). On the other hand, the biomass from cladodes contains high organic matter but low 49 nitrogen (Jigar et al., 2011), therefore it needs to be mixed with other feedstocks richer in nitrogen

Page 4 of 43

50 content, such as manure (Valenti et al., 2020), in order to maximise the biogas production in terms 51 of methane content (Varnero & de Cortázar, 2013, Valenti et al., 2018b). Furthermore, waste 52 material from OFI crop pruning can also be used as a feedstock to produce biogas and biofertilizers 53 through the anaerobic digestion process, within the concept of Biogasdoneright<sup>©</sup> (Dale et al., 54 2016). With regard to this concept, the by-products (i.e., waste material from OFI crop) can be used 55 for producing biogas in a more sustainable way (Valenti et al., 2017; Selvaggi & Valenti, 2021). 56 Based on the various possibilities offered by the valorisation of this crop (Feyisa et al., 2022), 57 it is therefore necessary to acquire information on productive capacity of OFI and its localisation at 58 the territorial level in order to evaluate its possible use for energy production. 59 In this context, several studies have been carried out on biomass-bioenergy systems in recent 60 years by using the GIS tool which makes it possible to both manage and analyse different types of 61 georeferenced information by adopting the concept of map-layers (Valenti et al., 2018c; Bambara et 62 al., 2019). Some research studies have covered subjects including biomass to biofuel feedstock and 63 conversion technologies, biomass supply chain design and management including modelling and 64 optimisation approaches (Ba et al., 2016; Ghaderi et al., 2016; Barbosa-Póvoa et al., 2017). Erre et 65 al. (2009) proposed a GIS-based methodology to analyse the capacity of adaptation of two local 66 biotypes of OFI (i.e., Opuntia ficus-indica (L.) Mill., and Opuntia amyclaea Ten) to different types 67 of land and environmental conditions. Land-use planning and strategic management in agriculture, 68 through the use of GIS tools, are effective tools to achieve sustainable development (Ghosh and 69 Kumpatla, 2022). Determination of the suitability of land-use types for a certain area, that is, setting 70 the priority of agricultural land-use types, is an important part of land-use planning (Akpinar et al., 71 2004).

The application of GIS tools has been widely proposed in several research studies aimed at
defining indices and indicators suitable for describing the potential production of biomass in
Mediterranean areas and for estimating the potential production of biogas (Valenti et al., 2016;

75 Valenti and Porto, 2019; Selvaggi et al., 2021). In these studies, the definition of the indicators was 76 carried out on the basis of crop coverage derived from digital cartography and orthophotos. 77 In other studies, the main objective concerned the analysis of the productivity of the plant 78 species in the examined area. Owen and Griffiths (2014) applied the Environmental Productivity 79 Index (EPI), computed by following the methodology proposed by Nobel and Meyer (1985), for the 80 development of a geospatial model aimed at estimating the bioethanol yield potential of four CAM 81 crops (i.e., Agave fourcroydes, Agave salmiana, Agave tequilana, and OFI) in Australia. In this 82 research, GIS software was utilised to combine climatic data with titratable acidity responses as a 83 function of photosynthetically active radiation (PAR), temperature and precipitation in order to 84 evaluate the influence of environmental conditions on the species distribution. However, in the 85 study OFI bioethanol yield potential was not computed, since it did not match the environmental responsibility (ER) criteria, defined by the authors, as a 'best' option to identify potential trial sites 86 87 outside areas that support high-yield agriculture (Owen et al., 2016).

88 Therefore, by defining tailored indices, this study aims at evaluating the feasibility of using 89 OFI biomass for anaerobic digestion and its territorial distribution, as well as estimating the biogas 90 and electricity potential production in a territorial area of Sicily. By following the methodology 91 proposed by Owen & Griffiths (2014), this study was carried out through the application of GIS 92 software and EPI model. Specifically, the aim was to express the prickly pear productivity based on 93 the soil and climatic variables of the considered territorial area. To this end, the province of Catania 94 was selected as the study area for the computation of the EPI for OFI, by taking into account the 95 necessary environmental parameters acquired by local weather stations during a 10-year time 96 interval. Furthermore, on the basis of the evaluated amount of potential biomass, the biogas per unit 97 of surface area and the electricity potentially obtainable per unit of surface area were computed by 98 taking into account the estimated EPI, the production of dry matter (DM), and the results of the 99 Biochemical Methane Potential (BMP) test.

100

# Computation of biomass, biogas, and bioenergy production from *O. ficus-indica* in the literature

104

105 As worldwide recognised, prickly pear has an excellent biomass production capacity still 106 under unsuitable soil and climate conditions, thanks to its high efficiency in the use of water (Santos 107 et al., 2016; Ramos-Suàrez & Martinez, 2014). However, the productivity of Opuntia is influenced 108 by the average temperature, and by solar radiation within the wavelength range between 400 and 109 700 nm. Opuntia plant dies at temperatures below -5 ° C and could survive at soil temperatures around 70 ° C, yet with permanent damage. The maximum production of Opuntia is reached within 110 111 the 5-20 °C range (Nobel, 2001). Furthermore, the biomass production from Opuntia is considered 112 stable over time because it is not affected by rainfall events that are irregularly distributed during 113 very dry periods (Santos et al., 2016).

Based on the main research studies found in the literature, Table 1 shows a comparison
between the main parameters due to the biogas production in different contexts.

116

117 Table 1. Main data and parameters from experimental analyses carried out on OFI.

118

Santos et al. (2016) compared different *OFI* varieties in Brazil and found that the average productivity of fresh biomass (raw matter) of prickly pear reached almost 90 t ha<sup>-1</sup> yr<sup>-1</sup> and the productivity of dry matter was equal to 8 t ha<sup>-1</sup> yr<sup>-1</sup>. Furthermore, they highlighted that, under favourable and suitable water irrigation conditions, prickly pear can reach up to 45-50 t ha<sup>-1</sup> yr<sup>-1</sup> of dry matter production, which could be considered a very high yield if compared to those of the most

commonly used crops for biomass production (Santos et al., 2016; Ramos-Suàrez & Martinez, 124 125 2014]. In cultivations of OFI located in Argentina it has been found that, in sandy soils and in those territorial areas characterised by 300 mm of rainfall, the productivity of dry matter ranged between 126 2.1 - 2.4 t ha<sup>-1</sup> yr<sup>-1</sup>, which corresponds to a mean rainfall-use efficiency factor (RUE) of 7.4 kg ha<sup>-1</sup> 127 128 yr<sup>-1</sup> mm<sup>-1</sup> of dry matter. These yield values are lower than those ones found for arid and sandy soils, 129 which are characterised by an average annual rainfall ranging between 200 and 400 mm, and by a yield of about 15 - 22.5 kg ha<sup>-1</sup> yr<sup>-1</sup> mm<sup>-1</sup>. On the contrary, on silty sand soils, with rainfall slightly 130 131 above 200 mm, the productivity of dry matter reached values of about 0.75 t ha<sup>-1</sup> yr<sup>-1</sup> and a mean rainfall-use efficiency factor (RUE) of only 3.5 kg ha<sup>-1</sup> yr<sup>-1</sup> mm<sup>-1</sup> (Guevara & Estevez, 2001). 132 The estimation of the theoretical potential of biogas production from the biomass of prickly 133 134 pear was carried out by Santos et al. (2016) by considering the average productivity value of the dry 135 biomass of three selected species, giant palm (Opuntia ficus-indica), palma redonda (Opuntia ficusindica) and palma miúda (Nopalea cochenillifera), which was equal to 7.9 t ha<sup>-1</sup> yr<sup>-1</sup>, with an 136 137 average value of volatile solids (VS) equal to 91%. Therefore, by taking into account all the abovementioned parameters, the potential biogas production was estimated to be 3717 m<sup>3</sup> ha<sup>-1</sup> yr<sup>-1</sup>. 138 139 Similar results of potential biogas production were found in the literature for other traditional energy crops such as maize (5780 m<sup>3</sup> CH<sub>4</sub> ha<sup>-1</sup>), alfalfa (3995 m<sup>3</sup> CH<sub>4</sub> ha<sup>-1</sup>), and forage beet (5800 140 141  $m^{3}$  CH<sub>4</sub> ha<sup>-1</sup>) (Santos et al., 2016). 142 Mason et al., (2015) compared different datasets for OFI, unfertilised rain-fed crops and a

Mason et al., (2015) compared different datasets for OFI, unfertilised rain-fed crops and a manual harvest, with limited availability of water. It was found that increased yields per hectare due to *greater planting densities could be achieved through mechanised harvesting*. Furthermore, the resilience of these plants to drought leads to a decrease in production rather than crop failure. Through the application of the methodology reported by Mason et al., (2015), on data elaborated from Gasston et al., (2013), the gas yield production was estimated to be 325 CH<sub>4</sub> l kg<sup>-1</sup> and electricity from biomass of dry matter was equal to 1.33 MWht<sup>-1</sup>.

De Cortazar & Nobel (1990) predicted EPI for 253 regions worldwide by using data from 1464 weather stations within 60° of the equator. First, the climatic data were used to calculate daily values of a PAR index, a temperature index, and a water index. In this research study, OFI productivity of 32 tons ha<sup>-1</sup> year<sup>-1</sup> was predicted for western South America with rainfall above 331 mm.

154 Comparetti et al., (2017) carried out a research work aimed at estimating the potential 155 production of biogas and, indirectly, biomethane or electrical and thermal energy in Sicily. As a 156 result, they found a biomass production from prickly pear equal to 8.5 t ha<sup>-1</sup> yr<sup>-1</sup> of dry matter with 157 an average annual rainfall of 300 mm, a value similar to Spain (Rosato, 2014), and by applying a 158 BMP value of about 300 Nm<sup>3</sup> t<sup>-1</sup>, the potential production of biogas was estimated.

Furthermore, a conversion factor suitable for estimating the amount of produced electricity was proposed by several authors (Ortiz-Laurel et al., 2014; Quadros et al., 2010; Pompermayer & Paula Junior, 2000). In detail, it was found that 1 m<sup>3</sup> of biogas containing about 60% methane allows the production of 1.25 kWh, therefore it was estimated that biomass from prickly pear allows an electrical energy production equal to 4646 kWh ha<sup>-1</sup> yr<sup>-1</sup>e and from the analysis of the produced biogas it has a calorific value equal 5500 kcal m<sup>-3</sup>, according to Pompermayer & Paula-Júnior (2000).

Obach & Lemus (2006) estimated a production of 23,400 kWh ha<sup>-1</sup> yr<sup>-1</sup> based on an average production of 300 t ha<sup>-1</sup> yr<sup>-1</sup> of raw matter, with a biogas potential production of 58 m<sup>3</sup> per t SV<sup>-1</sup> (with the 52% of methane content) and 1.5 kWh m<sup>-3</sup> of electrical energy. Furthermore, by considering that the average electricity consumption of a Brazilian household is equal to 200 kWh month<sup>-1</sup>, biomass from prickly pear would allow the sufficient production of electricity to meet the annual consumption of about two houses (Santos et al., 2016).

Table 1 highlighted that many studies in the field did not evaluate the potential biogas
production as well as the electricity from biomass. Therefore, in the research outlined in this paper,

174	the computation of biomass, biogas, and bioenergy production from OFI aims at contributing to the
175	needed increase of knowledge in the field, as highlighted in this state of the art from the literature
176	studies.

177

#### **3 Materials and methods**

The methodology applied in this study was carried out through the following steps, accordingto Owen & Griffiths (2014):

Analyses and elaborations of data related to precipitation, PAR, and average values of the
 minimum and maximum temperatures acquired by the weather stations located in the area,
 in order to define eco-physiological indices useful for the EPI computation;

- 2. Analyses of the soil characteristics nearby the weather station, by evaluating the clay, silt
  and sand values of the soils in order to define the soil water retention, in order to define an
  eco-physiological index useful for the EPI computation;
- 187 3. Computation of the eco-physiological indices, through the use of the ArcGIS® software, in
  188 order to estimate EPI by taking into account variations of solar radiation, water content,
  189 and temperatures;
- 4. Application of *kriging* interpolation tool of GIS software, to produce tailored maps with
  the aim of showing the EPI distribution at the territorial level;
- 192 5. Estimation of the potential production of biogas, by using the ArcGIS® software, based on
  193 literature data related to both the biomass production and its yield;
- 6. Estimation of the electricity production based on both the estimated potential production of
  biogas and literature data (e.g., biogas-electricity conversion factors).

## 196 3.1 Definition of eco-physiological indices and computation of the Environmental 197 Productivity Index (EPI)

Based on the methodology proposed in many research studies (Nobel & Meyer, 1985; Nobel,
1988; Nobel & Quero, 1986), the first step of the study provides forecast information on the
biomass productivity and makes it possible to determine these values in different areas, different
climatic conditions, and different soils.

202 EPI depends on the minimum and maximum temperature (through the *temperature index* I<sub>t</sub>),

203 rainfall (through the *rainfall index* I<sub>w</sub>) and PAR, as a fraction of solar radiation, (through the

204 Ecophysiological response to PAR index I<sub>p</sub>), and it was calculated by applying the following

205 equation (de Cortázar & Nobel, 1986; Nobel, 1988; Nobel & Valenzuela, 1987; Nobel, 1989):

$$206 \qquad EPI = I_W \times I_t \times I_p \tag{1}$$

In detail, the EPI was computed as an annual average value by using monthly data. The EPIequation was the following:

209 
$$EPI_{annual} = \sum_{m=1}^{12} \frac{(I_W \times I_t \times I_p)_m}{12} = \frac{I_W^{JAN} \times I_t^{JAN} \times I_p^{JAN} + \dots + I_W^{DEC} \times I_t^{DEC} \times I_p^{DEC}}{12}$$
(2)

210 where m is related to the month of the year.

In the following section the contribution provided by the individual parameters adopted forthe EPI calculation is detailed.

#### 213 3.1.1 <u>Rainfall and soil texture parameters</u>

In order to compute the EPI it was necessary to evaluate the relationship between rainfall andthe current water availability in terms of soil water potential.

216 The soil water potential ( $\Psi$ s) has mainly negative values, therefore a high potential requires a 217 low water retention capacity, and a low energy is required to the plants for the absorption. On the contrary, if the soil water potential is low, the soil strongly holds water, and a considerable effort toabsorb water is required to plants.

Furthermore, the soil water potential depends on rainfall and soil texture, therefore the
necessary analyses for EPI estimation, required data on soil texture, i.e., the calculation of the clay,
sand, and silt fraction, neglecting the value of the soil organic fraction.

According to Nobel (1988), CAM plants are very sensitive to the lack of water in the soil and

their soil water absorption commonly takes place between -0.2 and -0.4 MPa for  $\Psi$ s and, under

- stress conditions, this value is around -0.5 MPa. Therefore, water absorption takes place when  $\Psi$ s > -0.5 MPa.
- 227 The soil water potential is computed as a function of the water content ( $\theta$ ) and texture classes 228 (C = clay; S = sand), by using the following equation (Acevedo et al., 1983):

229 
$$\Psi_s = A \times \vartheta^B \tag{3}$$

230 in which A and B depend on soil textures through the following relations:

231 
$$A = 100 \exp[a + b(\%C) + c(\%S)^2 + d(\%S)^2(\%C)]$$
(4)

232 
$$B = e + f(\%C)^2 + g(\%S)^2 + g(\%S)^2(\%C)$$
(5)

where the parameters a, b, c, d, e, f, and g were obtained from Saxton et al. (1986).

The computation of the gradient function  $(g_{i,soil})$  for each single type of soil was carried out by means of a linear proportion between the  $\theta_{sandy soil}$  and  $g_{i,sandy soil}$  while the following equation (Eqn. 6) is considered valid for a wide range of textures and for h values within unsaturated soil conditions (Saxton et al., 1986). Consequently, the day-duration (U<sub>days</sub>) was estimated as a function of precipitation R, when the condition  $\Psi$ s>-0.5 MPa occurs, by the following equation:

239 
$$U_{days} = g_i \times R \tag{6}$$

The effective number of days per month (U<sub>e</sub>) when plant carbon uptake is not rate-limited by
water availability was determined by the following equation:

Page 12 of 43

242 
$$U_e = g_i \times R \times f_d \tag{7}$$

where  $f_d = 1.92$  for OFI and identifies the value of the titratable plant acidity (TA) within a phase of water deficit through the calculation of the ratio between titratable plant acidity under drought conditions (TA<sub>d</sub>) and TA under optimal conditions, by considering a 28-day interval (Acevedo et al., 1983; Saxton et al., 1986; Nobel and Valenzuela, 1987; Nobel, 1989).

Finally, the rainfall index I<sub>w</sub> was computed by the following equation:

$$I_w = U_e / D_m \tag{8}$$

where  $D_m$  is the number of days in a month. Therefore, it was established that  $I_w = 1$  when  $U_e/D_m \ge 1$  (Nobel, 1988).

#### 251 3.1.2 <u>Temperature parameters</u>

The carbon absorption capacity of *OFI* demonstrates that this plant is strongly affected by temperatures. Therefore, the definition of the temperature index  $I_t$  aims at representing this absorption capacity based on temperatures during both day and night.

Consequently, the analysis of both the monthly minimum night-time temperatures  $I_t min$  and the monthly maximum day-time temperatures  $I_t max$  was necessary to determine the temperature index  $I_t$ , by applying the following equations (Nobel, 1988; 1989; Nobel & de Cortázar, 1991; Nobel & Israel, 1994):

259 
$$I_{t min} = -0.0041 t_{min}^2 + 0.117 t_{min} + 0.186$$
 (9)

260 
$$I_{t max} = -0.0002t_{max}^2 + 0.0104t_{max} + 0.875$$
 (10)

$$I_t = I_{t \min} / I_{t \max}$$
(11)

#### 262 3.1.3 <u>Photosynthetically Active Radiation parameter</u>

263	In previous research studies carried out on OFI it was found that the CO <sub>2</sub> absorption during
264	night-time, as well as the increase of acid concentration, and their ratio are influenced by the
265	amount of PAR that the plant is able to absorb during the day (Nobel & Hartsock, 1983; de Cortázar
266	& Nobel, 1986).
267	Therefore, the <i>Ecophysiological response to photosynthetically active radiation index</i> $I_p$
268	depends on PAR and it was computed according to the following equation (Nobel and Valenzuela,
269	1987; Nobel et al., 1987; Nobel, 1988; Nobel & de Cortázar, 1991; Nobel & Israel, 1994):
270	
271	$I_P = -0.0007p^2 + 0.057p - 0.1856 $ <sup>(12)</sup>
272	
273	in which p stands for the PAR value. When $p \ge 35 \mod m^{-2} day^{-1}$ , the index I <sub>P</sub> was set equal to
274	1.
275	3.2 Evaluation of potential production of biomass, biogas, and electricity from <i>OFI</i>
276	In order to estimate the amount of potential biogas per unit of surface area, after the

computation of the EPI, it is necessary to take into account the data related to the dry matter contentas well as the BMP tests of the species.

- 279 The biomass yield or potential biomass production (P) of *OFI*, expressed in  $[t \ yr^{-1}ha^{-1}]$ ,
- 280 was estimated by the following equation, as the product of the EPI and the maximum dry matter
- 281 productivity  $(P_{max})$  expressed in t per hectare and per year, by considering optimal irrigation
- conditions and a value of 8 t ha<sup>-1</sup> yr<sup>-1</sup> for irrigation plant density:

$$P = P_{max} \times EPI \tag{13}$$

Page 14 of 43

In this equation, the value of  $P_{max}$  was considered equal to 8.5 t ha<sup>-1</sup> yr<sup>-1</sup>, in accordance with other research studies carried out on the same territorial area (Comparetti et al., 2017). Furthermore, by considering the pessimistic value of BMP, i.e., equal to 300 Nm<sup>3</sup> t<sup>-1</sup> of dry matter per year, the total potential production of biogas (B) expressed in Nm<sup>3</sup> per hectare and per year can be obtained by the following relation:

$$B = P \times BMP \tag{14}$$

Additionally, the potential production of electricity obtainable from biogas-conversion was computed by using the conversion factor proposed by Pompermayer & Paula-Júnior (2000) for the estimation of electricity. In detail, since a cubic meter of biogas containing about 60% of methane allows the production of 1.25 kWh, the electric energy production  $P_{eep}$  for one year expressed in  $[kWh yr^{-1} ha^{-1}]$  was estimated by the following relation:

295 
$$P_{eep} = 1,25 \times B$$
 (15)

Next, the computation of the surface area *S* in terms of hectares of each considered municipality,
allows achieving the potential total production of biogas and electricity per municipality by using
the following relations, respectively:

$$Btot = P \times BMP \times S \tag{16}$$

 $300 \qquad P_{eeptot} = 1,25 \times Btot \tag{17}$ 

#### 301 4 Case study

The study was carried out in the Province of Catania. Catania province covers an area of 3,552 km<sup>2</sup>, includes 58 municipalities and is located on the east coast of the island. It is characterised by the presence of Etna, one of the largest active volcanoes in the Mediterranean area, which reaches 3,350 m a.s.l. (Carbone et al., 2009). Page 15 of 43

The average temperature within Sicilian region is quite high everywhere, ranging from 19°C of the coastal areas to 13°C of the higher inland areas. January is the coldest month and has a temperature value close to the coastal areas of about 10°C, as it is influenced by the sea. The month of July is the hottest one with an average value of temperature that ranges from 25-26°C, close to the coastal areas, to 18°C in the mountainous ones (Venturella, 2004).

311 The province of Catania offers a great climatic variety, which is influenced by the altitude and the 312 proximity to the sea (Carbone et al., 2009). The area of the Catania Plain has a semi-dry climate 313 with low precipitations, mostly concentrated during the autumn season. Moreover, this area is 314 characterised in all seasons by a strong temperature range from day to night. The coastal area is 315 characterised by very hot summer season and mild winter, with rainfall mainly concentrated in the 316 autumn-winter period. Conversely, in the internal areas the winter temperatures are lower than those 317 recorded in the coastal zone, while summer ones are quite similar (Carbone et al., 2009; Leanza et 318 al., 2022).

Furthermore, based on a study carried out by the Agriculture and Forestry Department of the Sicilian region on the analysis of data from 1965 to 1994, in the province of Catania three main areas can be distinguished based on the average yearly temperatures: the coastal and plain areas, belonging to the municipalities of Acireale, Catania, Piedimonte Etneo, and Ramacca, with values of about 18°C; the internal hilly area belonging to the municipalities of Mineo and Caltagirone which reported yearly temperatures of 16-17°C; and the volcanic area, where the temperature values decrease with altitude (Cartabellotta et al., 1998).

With regard to rainfalls, the highest annual values (about 960 mm) in the whole Sicily are recorded on the eastern and north-eastern territorial areas of Etna, with a value that proportionally increases with altitude, reaching about 1200 mm at the top of Etna. On the contrary, very low annual rainfall values (about 500 mm) are found on the western and south-western territorial areas of Etna, particularly in the municipalities of Paternò, Motta Sant'Anastasia, Maniace, and Ragalna.

Page 16 of 43

331 Low annual rainfall values (about 500 mm) are recorded in the south of the province ranging from 332 402 mm in Ramacca municipality to 579 mm in Mirabella Imbaccari municipality. The other values 333 acquired from the weather stations located in Caltagirone, Mineo, and Vizzini municipalities ranged 334 between the above-reported values (i.e., 402 and 579 mm) (Cartabellotta et al., 1998). 335 Moreover, based on the surveys carried out in Sicily by the Ministry of Economic 336 Development, 1 million m<sup>3</sup>, 2.5 million m<sup>3</sup>, and 7.2 million m<sup>3</sup> of natural gas are used by industries, 337 to produce thermal and electrical energy, and for domestic heating, respectively (Comparetti et al., 338 2017). In this regard, the potential biogas production from biomass of OFI could contribute to meet 339 the demand for natural gas.

#### 340 4.1.1 <u>Environmental productivity index (EPI) within the study area</u>

341 Twenty-three regional weather stations (Table 2; Figure 1), managed by the Sicilian Agro-342 meteorological Information Service (SIAS), were taken into account in this study. The weather 343 stations acquire climatic data, such as air temperature and PAR, at different locations and the 344 Service provides them to the users at various granularities.

#### 345 Figure 1 – Localisation of weather stations within the study area.

- 346 Table 2 WGS84 geographical coordinates of the weather stations and related provinces
- 347

Among these weather stations, 14 are located in the Province of Catania and 9 are located in the other neighbouring provinces (i.e., Messina, Enna, Syracuse, Ragusa, and Caltanissetta). The considered number of weather stations has proven to be adequate in order to obtain a uniform distribution of data throughout the territory with a good coverage in coastal and mountainous areas. Furthermore, the decision to include in this study weather stations located outside the Province of Catania was due to the need to determine a good data spatial coverage also in those areas located close to the administrative boundaries.

```
Page 17 of 43
```

355	In detail, the daily average data of maximum and minimum temperatures, rainfalls and PAR,
356	recorded from 1 January 2006 to 1 January 2016 were elaborated.
357	The PAR index was computed from the solar radiation data, acquired from SIAS database,
358	and expressed in (MJ m <sup>-2</sup> ), by assuming that 48% of the incident beams fall within the action-
359	interval between 400 and 700 nm (Weiss & Norman, 1985).
360	For evaluating the clay, silt, and sand values of the soils in which weather stations are located, the
361	following maps were taken into account for GIS analyses:
362	- Italian map of the clayey soils provided by the Ministry of University and Scientific and
363	Technological Research and by the National Research Council, which was carried out based
364	on 1985-cartography;
365	- The Dominant Surface Textural Class of STU map provided by the European Soil Data
366	Center (ESDAC), https://esdac.jrc.ec.europa.eu/;
367	- The Topsoil physical properties for Europe map developed by the European Soil Data
368	Center (ESDAC);
369	- The Harmonized World Soil Database (v 1.2) (FAO/IIASA/ISRIC/ISSCAS/JSR, 2012),
370	https://www.fao.org/soils-portal/soil-survey/soil-maps-and-databases/harmonized-world-
371	soil-database-v12/en/.
372	The Harmonized World Soil Database (HWSD), in particular, made it possible to define the
373	fractions of clay, silt and sand of Topsoil, which represents the soil layer between 0 and 30 cm
374	depth. Results of these elaborations are reported in Figure 2.
375	
376	Figure 2 – Soil type distribution based on HWSD data. a) Distribution at regional level within Sicily region. b) Distribution
377	at provincial level within the study area (i.e., Catania province).
378 379	The twenty-three weather stations were georeferenced in GIS as shown in Figure 1. In detail
380	the geographical coordinates of the weather stations were acquired and transformed into a new
	16

Page 18 of 43

vector layer (*point as feature*). The obtained map was overlaid to the map reporting the soil types
(Figure 2b), in order to define their soil texture.

383 On this basis, for each selected soil texture associated to the weather stations, the soil water content 384 was computed, according to Saxton et al. (1986), by setting the soil water potential equal to  $\Psi s =$ 385 0.5 MPa. By assuming that each soil can be defined through the parameter  $g_i$  as a function of the 386 soil water content when  $\Psi$ s =-0.5 MPa and, by considering a linear relationship between  $\Psi$ s and 387 precipitation (Nobel et al., 1987; Nobel, 1988), each type of soil was compared to the rainfall R 388 (mm) and duration (in days), and only when  $\Psi$ s exceeded the values of -0.5 MPa, the types of soil 389 were also compared to the behaviour of sandy soils as defined by Nobel and Venezuela (1987). 390 The point data, defined as EPIannual and computed for each weather station, were then 391 interpolated by using, among the stochastic methods, the *Kriging* tool, available in GIS software, in order to determine the EPIannual value over the whole study area. 392

In this regard, as reported in the literature, it has been observed that when the amount of acquired data results high, and with a well distribution over the territorial areas, all methods, both deterministic ones (i.e., IDW, spline) and stochastic ones (i.e., kriging and co-kriging), of spatial estimation and analysis result acceptable. On the contrary, only in the case of complex morphotopographic characteristics, with low data acquired due to the number of weather stations, stochastic methods for minimising the possible estimation errors should be applied (Fiorenzo et al., 2008).

The monthly values of the  $I_w$ ,  $I_t$  and  $I_p$  indices were computed over a 10-year period (2006-2015) and reported in ArcGIS<sup>®</sup> to produce the map of the EPI distribution within the study area. Then, by means of the *Kriging* tool, the interpolation of the monthly indices was carried out, producing 12 maps, for each considered indicator ( $I_{w_gen}$ ,  $I_{w_feb}$ , ...,  $I_{w_dic}$ ;  $I_{t_gen}$ ,  $I_{t_feb}$ , ...,  $I_{t_dic}$ ;  $I_{p_gen}$ ,  $I_{p_feb}$ , ...,  $I_{p_dic}$ ).

404	Next steps involved the use of the ArcGIS <sup>®</sup> map algebra tool to compute the monthly EPI,
405	related to each month of the year (i.e., <i>EPI_January; EPI_February; EPI_March</i> , etc.) and then the
406	computation of annual EPI, according to Eqn. 1.
407	The raster file of EPI distribution was then firstly converted into weighted points with values
408	ranging between 0 and 1, based on the index, and then overlaid with municipality boundaries of the
409	Province of Catania. In detail, the vector layer contained polygons that represent the surface area of
410	each municipality.
411	As a result, for each municipality a new layer was defined containing both the weighted
412	points with values ranging between 0 and 1, and the adopted EPI weights with the aim of
413	computing for each municipality, the average EPI value.
414	Finally, the EPIannual index was applied to compute, per year and per hectare, the potential
415	production of biogas, by adopting the value that represents the maximum dry biomass productivity
416	(P), according to Equation 13.

#### 417 **5 Results and discussion**

#### 418 5.1 Environmental productivity index (EPI)

Nine different soil types were found in the study area, i.e., Etna volcanic cone, *alluvional plains*, *coastal plains*, *arenaceous reliefs*, *carbonate reliefs of the Hyblaean hill*, *clayey-marly hilly reliefs*, *hilly reliefs with chalky or carbonate crests*, *hilly reliefs with sandy hills at the summit*, *Hyblaean Vulcanites*. In terms of soil texture, 65% of the considered twenty-three weather stations falls on soil classified as loam, 30% on sandy loam soil, 5% on loamy sand soil. Within these considered *soil types*, the percentage content of clay ranged from a minimum of about 6% in the loamy sand soils in the weather station located in Bronte municipality, to a maximum of 26% for the loam soils recorded for the weather station of Ramacca municipality. Conversely, the sand content ranged
from a minimum value of 32% in the loam soils to a maximum value of 83% in the loamy sand
soils (i.e., Bronte municipality).

The soil water potential had an average value of water content equal to 1077.21 mm at  $\Psi_s$  =-429 430 0.5 MPa and increased in soils characterised by a lower clay content. The minimum value of 79.18 431 mm was measured in Bronte municipality (i.e., loamy sand soil) whereas the maximum value equal to 3282.26 mm in the municipality of Ramacca (i.e., loamy soil). Furthermore, in Bronte 432 433 municipality the minimum value of  $g_i$ , equal to 0.3370 was recorded, whereas the maximum  $g_i$ 434 value equal to 0.6545 was found in Ramacca. Therefore, based on data elaboration, the highest 435 value of the gi was found in the loamy soils, i.e., in the municipalities of Ramacca, Caltagirone, 436 Mineo, Maletto, Linguaglossa, Riposto, and Adrano.

Furthermore, it emerged that, within all the territorial areas in which the weather stations are located, the  $I_w$  index resulted equal to 1 during the months of January, February, March, October and December, in some years also in April (i.e., 2012, 2013), in September (i.e., 2009, 2010, 2011) and in November (i.e., 2007, 2009, 2011).

441 Conversely, this index I<sub>w</sub> assumed a value equal to zero, in most of the territorial areas in 442 which the weather stations are located, in the months of June (during the years 2012 and 2013), July 443 in the year 2011, and August (during the years 2011 and 2014). Therefore, the wettest municipality 444 was Linguaglossa and the driest Ramacca.

During the calculation of the I<sub>P</sub> index, the value of I<sub>P</sub>=1 was always found during the entire time interval (i.e., 10 years) in the months of April, May, June, July, August and September, and only for the years 2012 and 2015 also during the month of March. The value of I<sub>P</sub><1 was found in the months of March and September only for the weather station located in the municipality of Pedara. The minimum PAR value of 5.06 mol m<sup>-2</sup> day<sup>-1</sup> was registered for the year 2011 during the month of November in the weather station located in Pedara municipality whereas the maximum 451 value of 29.01 mol m<sup>-2</sup> day<sup>-1</sup> was found during the month of June in the weather station located in
452 Gela municipality, which is a weather station located outside the provincial administrative
453 boundaries.

454 The results of the I<sub>T</sub> computation showed values between -0.75 and 1 as minimum and 455 maximum values, respectively. During the interval April-October and for some years also during 456 the month of November, higher average values of the I<sub>T</sub> were found. Therefore, it was observed that OFI showed higher values of CO<sub>2</sub> potential absorption at different daily T<sub>max</sub> values (Owen and 457 458 Griffiths, 2014). In general, a low night temperature and the resistance to variations in temperatures 459 between day and night demonstrated that the species has a greater suitability in southern latitudes as 460 characterised by these considerable variations in temperature within the same season (Owen et al., 461 2016). The lowest average value for the minimum temperature was found in the weather station located on the Etna volcano, while the highest average value for the minimum temperature was 462 463 found in the municipality of Ramacca, which is located at 270 m a.s.l. and at about 45 km-distance 464 from the coast. The lowest average value for the maximum temperature was found in Maletto 465 municipality (960 a.s.l. on the north-west side of the Etna volcano) while the highest one was recorded in the municipality of Paternò (225 m a.s.l., at 18 km-distance from the coast). 466 467 Recorded data were elaborated and reported in the GIS software to produce the EPI map. 468 Figure 3 shows the index distribution at the territorial level within the whole province of Catania

where EPI values ranged between 0.47 and 0.57. Therefore, the maximum EPI value was less than0.60 as found by Owen & Griffiths (2014).

The most suited areas for *OFI* were found in the south-west (currently the commercial production area of *OFI*), in the north-eastern and north-western areas of the province, and also in those territorial areas close to the administrative boundaries between the provinces of Catania and Messina. In detail, the municipalities of Mirabella Imbaccari, Raddusa, San Cono, Mineo,

Page 22 of 43

475 Grammichele, Calatabiano, Fiumefreddo, Caltagirone, Castel di Iudica, Piedimonte, Mascali,

476 Giarre, Santa Venerina and Maniace were selected as the most suitable areas.

On the contrary, the area of the Catania plain, the area at the top of the volcano, and the area
located to the south-east close to the administrative boundaries between the provinces of Catania
and Ragusa, were identified with a low suitability value. In detail, the municipalities of Catania,
Misterbianco, Paternò, Belpasso, Camporotondo, Tremestieri Etneo, Mascalucia, Santa Maria di
Licodia were selected as the less suitable areas.

482 The municipalities with a high EPI value were found to have an average monthly rainfall 483 ranging between 40.00 mm and 80.00 mm. These values are rather moderate in comparison to those 484 recorded in the other municipalities and contribute, together with the soil characteristics (i.e., high 485 value of g<sub>i</sub>), to reach a high value of I<sub>W</sub> indicator during the EPI calculation. Conversely, high 486 rainfall that will theoretically raise the EPI value would not produce high yields of OFI within the 487 considered territorial areas, since they are characterised by sandy loam or loamy sand soils and 488 therefore low I<sub>w</sub> values. As regard soils with a high clay content, that provides low values of water 489 absorption, these do not contribute for reaching optimal EPI values. In this regard, it has been found 490 that soil texture and rainfall are the main factors affecting the productivity of OFI (Guevara & 491 Estevez, 2001). In a previous study (Leanza et al., 2022), also the maximum temperature and the 492 altitude were relevant factors for the estimation of OFI probability of presence.

Within the most suitable municipalities, the monthly average values of the minimum temperatures were the highest, whereas the average values of the maximum temperatures were found similar to those ones registered for the other municipalities of the province. This latter result, found for the maximum temperatures, applies also for the monthly average value of the PAR that, in the most suitable municipalities, was recorded as being equal to 16.80 mol m<sup>-2</sup> day<sup>-1</sup>, which is a value close to those registered in the other municipalities of the province. Therefore, it is possible to

highlight that the minimum average temperature affects the carbon absorption, unlike the maximumaverage temperature and the PAR.

501 By analysing other research studies carried out in Sicily (Comparetti et al., 2017), it was 502 observed that this region could be highly exploited for agro-energy crops, especially for the 503 cultivation of OFI, in marginal areas currently not dedicated to cultivation. Marginal are considered 504 those areas where agricultural utilisation has lowered due to various issues, such as population 505 decrease, reduction of agricultural employment, reduced services, and degraded areas. In detail, in 506 these areas cultivation can reach about 600,000 hectares (ISTAT, 2011), at an altitude lower than 507 700 m a.s.l., with a temperature that rarely drops below 0°C, and a slope ranging between 5% and 508 35% (Comparetti et al., 2017). These results are in line with those acquired in a previous research 509 (Leanza et al., 2022) where good potential for OFI presence was found in hilly territories, having an 510 altitude ranging from approximately 200 m to 600 m.

511 By considering the computed values of the EPI, it is possible to evaluate the productivity of 512 potential biomass and, therefore, a better estimation of the amount of biogas potential production.

513 In Figure 4, the average value of the EPI provides an estimation of the index per m<sup>2</sup> of surface 514 area in each municipality.

515

516 Figure 3 – EPI yearly value distribution within the whole province of Catania.

517 518

Figure 4 – EPI yearly value distribution within the municipalities of Catania province.

#### 519 5.2 Potential biogas and electricity production within the study area

520 The potential biomass production was computed per hectare for each municipality and its 521 distribution was reported in Figure 5. The municipality with the lowest production of biomass was 522 Motta Sant'Anastasia (3.86  $t yr^{-1}ha^{-1}$ ) followed by the municipalities of Misterbianco, Paternò,

Page 24 of 43

523 Catania, Belpasso, and Camporotondo Etneo, which are mostly located within the inner areas of the 524 province (i.e., Catania plain). Low values of biomass production per hectare were also found in 525 those municipalities situated on the slopes of Etna volcano. In detail, territorial areas located in the 526 southern area of the volcano resulted less suitable than those located in the northern area. 527 The outcomes of the analyses proved that the soils located close to the Caltagirone 528 municipality were found as the most suitable ones. In detail, the municipality of Raddusa registered 529 the highest biomass production per hectare, equal to 4.50 t  $yr^{-1}ha^{-1}$ , followed by the 530 municipalities of Mirabella Imbaccari, San Michele di Ganzaria, Grammichele, San Cono, and 531 Mineo. With regard to the municipalities belonging to the Ionian coast, Giarre, Calatabiano, 532 Fiumefreddo, Riposto and Mascali resulted the most suitable ones. 533 In Figure 6, the distribution of the potential biogas produced was reported for the province of 534 Catania. It was computed by taking into account and combining the EPI values and data from the 535 literature on the potential biomass production and its capacity to produce biogas. Municipalities 536 were classified by using the method that adopts the data division into predefined groups, which are 537 established prior to data classification. This classification method was used for showing both the biogas potential biogas and the electricity distribution at territorial level (Figure 6 and Figure 7). In 538 539 detail, Figure 6 shows that the Caltagirone municipality represents the best territorial area for an 540 excellent potential biogas production, followed by the municipalities of Ramacca, Mineo, 541 Randazzo, and Bronte. 542 543 *Figure 5 - Distribution of the potential biomass production computed per hectare.* 

544 545

Figure 6 – Distribution of potential biogas production in the municipalities of Catania province.

- 546
- 547 Figure 7 Distribution of potential electricity production per year and hectare.

Page 25 of 43

549 According to the last step of the methodology reported in this study, the potential biogas production and electricity production per hectare were evaluated to be 1240.99  $Nm^3 vr^{-1}ha^{-1}$  and 550 1551.24 kWh yr<sup>-1</sup>, respectively, based on a computed average biomass production from OFI551 equal to 4.14 t  $yr^{-1}ha^{-1}$  (Figure 6 and Figure 7) 552 553 These results are in line with those obtained by Comparetti et al., (2017). In detail, in their research study, a biomass production equal to 2500 (10<sup>3</sup>t), biogas production of 87,500 (10<sup>3</sup>m<sup>3</sup>). 554 biomethane production of about 49,000 (10<sup>3</sup> m<sup>3</sup>), electricity production of 9583 (MWh), and 555 556 thermal energy production of 10.062 (MWh) were computed for the province of Catania. Therefore, the results reported by Comparetti et al., (2017) applied to an area of 600,000 ha, as in this study, 557 would produce an estimation of the average biomass production from OFI equal to 4.17 t  $yr^{-1}h$ 558  $a^{-1}$ , close to that obtained in this study, thus confirming the suitability of the methodology. 559

#### 560 6 Conclusions

In this study, the objectives aimed at defining the potential biomass production of OFI, its 561 562 theoretical potential production of biogas, and therefore the potential electricity production were 563 achieved by applying tailored indices, based on local values of climate variables and geospatial analyses. The use of GIS software allowed the visualisation at the territorial level of bioclimatic 564 565 data recorded by 23 selected weather stations within the study area, during a 10-year time interval, the elaboration of the acquired data by spatial analysis tools, and the computation of the EPI. In 566 567 addition, the results achieved from GIS analyses, allowed the identification of the most suitable 568 territorial areas for producing biogas from OFI, and an estimation of electricity production per year 569 and per hectare. Based on the outcomes, the combination of the methodology and tools, applied at 570 the territorial level, allowed increase of knowledge on the use of the OFI biomass residues for a 571 sustainable production of both electricity and biogas in the Mediterranean area. Further studies

- 572 could be focused on coupling the results of potential biomass production with geostatistical
- 573 analyses of species presence based on various predictors.

#### 574 Author contributions

575	Paola Maria Leanza: Methodology, Software, Validation. Francesca Valenti: Data
576	curation, Writing- Original draft preparation, Writing- Reviewing and Editing. Provvidenza Rita
577	D'Urso: Writing- Reviewing and Editing. Claudia Arcidiacono: Conceptualization, Writing-
578	Reviewing and Editing, Supervision.

#### 579 **Conflict of interest statement**

The authors declare that they have no known competing financial interests or personalrelationships that could have appeared to influence the work reported in this paper.

#### 582 Acknowledgements

The research study was carried out within the project: '*Piano incentivi per la ricerca di Ateneo 2020-2022* – 'Engineering solutions for sustainable development of agricultural buildings and land' (ID: 5A722192152) coordinated by Professor Claudia Arcidiacono; and it is in line with the project '*PON "RICERCA E INNOVAZIONE" 2014 – 2020, "Miglioramento delle produzioni agroalimentari mediterranee in condizioni di carenza di risorse idriche –* WATER4AGRIFOOD", CUP: B64I20000160005'. Authors are grateful to the Sicilian Agro-meteorological Information Service (SIAS) for providing climatic data.

#### 590 **References**

Acevedo, E., Badilla, I., & Nobel, P.S. (1983). Water relations, diurnal acidity changes, and
 productivity of a cultivated cactus, Opuntia ficus-indica. *Plant Physiology*, 72(3), 775-780.

593	2.	Aosaar, J., Varik, M., & Uri, V. (2012). Biomass production potential of grey alder (Alnus
594		incana (L.) Moench.) in Scandinavia and Eastern Europe: a review. Biomass Bioenergy, 45,
595		11-26.
596	3.	Akpinar, N., Talay, I., & Gun, S. (2004). Priority setting in agricultural land-use types for
597		sustainable development. Renewable Agriculture and Food Systems, 20(3), 136-147.
598	4.	Ba, B. H., Prins, C., & Prodhon, C. (2016). Models for optimization and performance
599		evaluation of biomass supply chains: An operations research perspective. Renewable
600		Energy, 87, 977-989.
601	5.	Bambara, L. D. F., Sawadogo, M., Roy, D., Blin, J., Anciaux, D., & Ouiminga. S.K. (2019).
602		Wild and cultivated biomass supply chain for biofuel production. A comparative study in
603		West Africa. Energy for Sustainable Development, 53, 1-14.
604	6.	Barbosa-Póvoa, A. P., da Silva, C., & Carvalho, A. (2017). Opportunities and challenges in
605		sustainable supply chain: An operations research perspective. European Journal of
606		Operational Research, 268 (2), 399-431.
607	7.	Carbone, S., Branca, S., & Lentini, S. (2009). Note illustrative della carta geologica d'Italia
608		alla scala 1:50000, Foglio 634 Catania. Università degli Studi di Catania, Dipartimento di
609		Scienze Geologiche Stampa S.EL.CA.s.r.l., Firenze.
610	8.	Cartabellotta, D., Drago, A., Lo Bianco, B., & Lombardo, M. (1998). Climatologia della
611		Sicilia. Regione Siciliana, Assessorato Agricoltura e Foreste, Palermo.
612	9.	Comparetti, A., Febo, P., Greco, C., Mammano, M.M., & Orlando, S. (2017). Potential
613		production of biogas from prinkly pear (oputia ficus- indica l.) in sicilian uncultivated areas,
614		Chemical Engineering Transactions, 58, 559-564.
615	10	Dale, B.E., Sibilla, F., Fabbri, C., Pezzaglia, M., Pecorino, B., Veggia, E., Baronchelli, A.,
616		Gattoni, P., & Bozzetto, S. (2016). An innovative new system is commercialized in Italy.
617		Biofuels Bioprod Biorefin, 10, 341-345.

618	11. de Cortázar, V. G., & Nobel P. S. (1992). Biomass and Fruit Production for the Prickly Pear
619	Cactus, Opuntia ficus-indica. J. AMER. Soc. HORT. SCI., 117(4), 558-562.
620	12. de Cortázar, V. G., & Varnero, M.T. (1999). Producción de energía. In G. Barbera, P.
621	Inglese & E. Pimienta, eds. Agroecología, cultivo y usos del nopal. FAO Plant Production
622	and Protection Paper, 132, 194-200, Rome
623	13. de Cortázar, V.G., & Nobel, P.S. (1986). Modeling of PAR Interception and Productivity of
624	a Prickly Pear Cactus, Opuntia ficus-indica L., at Various Spacings1. Agron. J., 78: 80-85.
625	14. de Cortázar, V.G., & Nobel, P.S. (1990). Worldwide environmental productivity indices and
626	yield predictions for a cam plant, Opuntia ficus-indica, including effects of doubled CO2
627	levels. Agricultural and Forest Meteorology, 49 (4), 261-279.
628	15. Erre, P., Chessa, I., Nieddu, G., & Jones, P.G. (2009). Diversity and spatial distribution of
629	Opuntia spp. in the Mediterranean Basin. Journal of Arid Environments 73:1058-1066.
630	16. ISTAT - National Institute of Statistics, 6th General Census of Agriculture, Sicilian Region,
631	Rome, Italy (2011). Available at: http://dati-
632	censimentoagricoltura.istat.it/Index.aspx?lang=it, accessed on October 2016.
633	17. FAO/IIASA/ISRIC/ISSCAS/JRC, Harmonized World Soil Database (version 1.2). FAO,
634	Rome, Italy and IIASA, Laxenburg, Austria (2012).
635	18. Feyisa, T., Tolera, A., Nurfeta, A., Balehegn, M., Yigrem, S., Bedaso, M., Boneya, M., &
636	Adesogan, A. (2022). Assessment of fodder resources in Ethiopia: Biomass production and
637	nutritional value. Agronomy Journal, 114, 8-25
638	19. Fiorenzo, F., Mancino, G., Borghetti, M., & Ferrara, A. (2008). Metodi per l'interpolazione
639	delle precipitazioni e delle temperature mensili della Basilicata. Forest@, 5, 337-350.
640	20. Ghaderi, H., Pishvaee, M. S., & Moini. A. (2016). Biomass supply chain network design: an
641	optimization-oriented review and analysis. Industrial Crops and Products, 94, 972-1000.

642	21. P. Ghosh, & S. P. Kumpatla, "GIS Applications in Agriculture", in Geographic Information
643	System. London, United Kingdom: IntechOpen, 2022. Available:
644	https://www.intechopen.com/online-first/81685 doi: 10.5772/intechopen.104786
645	22. Guevara, C. J., & Estevez, R.O. (2001). Opuntia spp. For fodder and forage production in
646	argentina: experiences and prospects in Cactus (Opuntia spp.) as forage. Produced within the
647	framework of the FAO International Technical Cooperation Network on Cactus Pear.
648	23. Jigar, E., Sulaiman, H., Asfaw, A., & Bairu, A. (2011). A. Study on renewable biogas
649	energy production from cladodes of Opuntia ficus indica. ISABB Journal of Food and
650	Agriculture Science, 1(3), 44-48.
651	24. Leanza, P.M., Valenti, F., D'Urso, P.R., & Arcidiacono, C. (2022). A combined MaxEnt and
652	GIS-based methodology to estimate cactus pear biomass distribution: application to an area
653	of southern Italy. Biofuels, Bioproducts & Biorefining, 16, 54-67.
654	25. Lee, M., Steiman, M., & St. Angelo, S. (2021). Biogas digestate as a renewable fertilizer:
655	Effects of digestate application on crop growth and nutrient composition. Renewable
656	Agriculture and Food Systems, 36(2), 173-181.
657	26. Mason, P. M., Glover K., Smith, J. A. C., Willis, K. J., Woods, J., & Thompson, I. P.
658	(2015). The potential of CAM crops as a globally significant bioenergy resource: moving
659	from 'fuel or food' to 'fuel and more food'. Energy Energy & Environmental Science, 8,
660	2320-2329.
661	27. Michel, J, Weiske, A., & Möller, K. (2010). The effect of biogas digestion on the
662	environmental impact and energy balances in organic cropping systems using the life-cycle
663	assessment methodology. Renewable Agriculture and Food Systems, 25, 204-218.
664	28. Nobel, P. S., & Hartsock, T.L. (1983). Relationships between Photosynthetically Active
665	Radiation, Nocturnal Acid Accumulation, and CO2 Uptake for a Crassulacean Acid
666	Metabolism Plant, Opuntia ficus-indica. Plant Physiol, 71(7), 1-75.

667	29. Nobel, P. S., & Meyer, S.E. (1985). Field productivity of a CAM plant, Agave salmiana,
668	estimated using daily acidity changes under various environmental conditions. Physiologia.
669	Plantarum, 65, 397-404.
670	30. Nobel, P. S., & Quero, E. (1986). Environmental productivity indices for a Chihuahuan
671	Desert CAM plant: Agave Lechuguilla. Ecology, 67, 1-11.
672	31. Nobel, P. S., & Valenzuela, A.G. (1987), Environmental responses of the CAM plant,
673	Agave Tequilana. Agricultural and Forest Meteorology, 39, 319-334.
674	32. Nobel, P. S., Russell, C. E., Felker, P., Medina, J. G., & Acuña, E. (1987). Nutrient
675	Relations and Productivity of Prickly Pear Cacti. Agron. J., 79, 550-555
676	33. Nobel, P. S. (1988). Environmental Biology of Agaves and Cacti. Cambridge University
677	Press, Cambridge, UK.
678	34. Nobel, P. S. (1989). Productivity of desert succulents. Excelsa, 14, 21-28.
679	35. Nobel, P. S., & de Cortázar, V. G. (1991). Growth and Predicted Productivity of Opuntia
680	ficus-indica for Current and Elevated Carbon Dioxide. Agron. J., 83, 224-230.
681	36. Nobel, P. S., & Israel, A. A. (1994). Cladode development, environmental responses of CO2
682	uptake, and productivity for Opuntia ficus-indica under elevated CO2. Journal of
683	Experimental Botany, 45(3), 295-303.
684	37. Obach, J. E., & Lemus, M. P. (2006). Bio energy generation using opuntia ficus indica in
685	arid and semi-arid zones of developing countries. In: Proceedings of Venice, Biomass and
686	Waste to Energy Simposium, Venice.
687	38. Ortiz-Laurel, H., Rössel-Kipping, D., & Kanswohl Norbert, N. (2014). Energy production
688	balance for biogas generation from cactus prickly in a staged biorefinery. International
689	conference of agricultural Engineering, Zurich.

690	39. Owen, A. N., & Griffiths, H. (2014). Marginal land bioethanol yield potential of four
691	crassulacean acid metabolism candidates (Agave fourcroydes, Agave salmiana, Agave
692	tequilana and Opuntia ficus-indica) in Australia. GCB Bioenergy, 6, 687-703.
693	40. Owen, A. N., Fahy, K. F., & Griffiths, H. (2016). Crassulacean acid metabolism (CAM)
694	offers sustainable bioenergy production and resilience to climate change. GCB Bioenergy, 8,
695	737-749.
696	41. Pompermayer, R., & Paula Junior, D.R. (2000). Estimativa do potencial brasileiro de
697	produção de biogás através da biodigestão da vinhaça e comparação com outros energéticos.
698	In Proceedings of the 3. Encontro de Energia no Meio Rural, Campinas (SP, Brazil).
699	42. Ramos-Suárez, J. L., & Martínez, N. C. A. (2014). Optimization of the digestion process of
700	Scenedesmus sp. And Opuntia maxima for biogas production. Energy Conversion and
701	Management, 88, 1263-1270.
702	43. Rosato, M.A., 2014, Il fico d'India: una biomassa trascurata. AgroNotizie - Notizie
703	agricoltura - tecnica, economia e innovazione.
704	http://agronotizie.imagelinenetwork.com/bio-energie-rinnovabili/2014/02/13/ilfico-
705	drsquoindia-una-biomassa-trascurata/36494.
706	44. Santos, N. T., Dutra, E. D. do Prado, A. G., Leite, F. C. B., de Souza, R. D. F. R., dos
707	Santos, D. C., Moraes de Abreu, C. A.M., Simões, D. A., de Morais, M. A. Jr., & Menezes,
708	R. S. C. (2016). Potential for biofuels from the biomass of prickly pear cladodes: Challenges
709	for bioethanol and biogas production in dry areas. Biomass and Bioenergy, 85, 215-222.
710	45. Saxton, K.E., Rawls, W.J., Romberger, J.S., & Papendisk, R.I. (1986). Estimating
711	generalized soil-water characteristics from texture. Soil Science Society America Journal,
712	50, 1031-1036.

- 46. Selvaggi, R., Valenti, F., Pecorino, B., & Porto, S. M. C. (2021). Assessment of tomato
  peels suitable for producing biomethane within the context of circular economy: A gis-based
  model analysis. *Sustainability*, 13 (10), 5559.
- 47. Selvaggi, R., & Valenti, F. (2021). Assessment of fruit and vegetable residues suitable for
  renewable energy production: GIS-based model for developing new frontiers within the
  context of circular economy. *Applied System Innovation*, 4 (1), 1-15.
- 48. Valenti, F., Porto, S.M.C., Chinnici, G., Cascone, G., & Arcidiacono, C. (2016). A GISbased model to estimate citrus pulp availability for biogas production: an application to a
  region of the Mediterranean Basin. *Biofuels, Bioproducts & Biorefining*, 10(6), 710-727
- 49. Valenti, F., Porto, S.M.C., Chinnici, G., Cascone, G., & Arcidiacono, C. (2017).
  Quantification of olive pomace availability for biogas production by using a GIS-based
  model. *Biofuels, Bioproducts & Biorefining*, 11(5), 784-797.
- 50. Valenti, F., Porto, S.M.C., Selvaggi, R., & Pecorino, B. (2018a). Evaluation of biomethane
   potential from by-products and agricultural residues co-digestion in southern Italy. *Journal of Environmental Management*, 223, 834-840.
- 51. Valenti, F., Porto, S.M.C., Dale, B.E., & Liao, W. (2018b). Spatial analysis of feedstock
  supply and logistics to establish regional biogas power generation: A case study in the
  region of Sicily, *Renewable and Sustainable Energy Reviews*, 97, 50-63.
- 52. Valenti, F., Zhong, Y., Sun, M., Porto, S.M.C., Toscano, A., Dale, B.E., Sibilla, F., & Liao,
- W. (2018c). Anaerobic co-digestion of multiple agricultural residues to enhance biogas
  production in southern Italy. *Waste Management*, 78, 151-157
- 734 53. Valenti, F., & Porto, S.M.C. Net electricity and heat generated by reusing Mediterranean
  735 agro-industrial by-products. *Energies*, 12 (3), 470.

/30	54. Valenti, F., Porto, S.M.C., Selvaggi, R., & Pecorino, B. (2020). Co-digestion of by-products
737	and agricultural residues: A bioeconomy perspective for a Mediterranean feedstock mixture.
738	Science of the Total Environment, 700, 134440.
739	55. Varnero, M. T., & de Cortázar, V. G. (2013). Production of bioenergy and fertilizers from
740	cactus cladodes in Chapter 8 Agro-industrial utilization of cactus pear. Food and
741	Agriculture Organization of The United Nations, Rome.
742	56. Venturella, G. (2004). Climatic and pedological features of Sicily. BOCCONEA 17, 47-53.
743	57. Weiss, A., & Norman, J.M. (1985). Partitioning solar radiation into direct and diffuse,
744	visible and near-infrared components. Agricultural and Forest meteorology, 34(2-3), 205-
745	213.
746	58. Yang, L., Lu, M., Carl, S., Mayer, J. A., Cushman, J. C., Tian, E., & Lin, H. (2015).
747	Biomass characterization of Agave and Opuntia as potential biofuel feedstocks, Biomass
748	and Bioenergy, 76, 43-53.
749	
750	
751	
752	
753	
754	
755	
756	
757	
758	
759	
760	
761	
762	
763	
764	
765	
766	
767	
/68	
/69	

770	
771	
772	
773	
774	
775	Figure legends
776	8 8
777	Figure 3 – Localisation of weather stations within the study area.
778	Figure 4 – Soil type distribution based on HWSD data. a) Distribution at regional level within Sicily region. b) Distribution
779	at provincial level within the study area (i.e., Catania province).
780	Figure 3 – EPI yearly value distribution within the whole province of Catania.
781	
782	Figure 4 – EPI yearly value distribution within the municipalities of Catania province.
783	Figure 5 - Distribution of the potential biomass production computed per hectare.
784	
785	Figure 6 – Distribution of potential biogas production in the municipalities of Catania province.
786	
787	Figure 7 – Distribution of potential electricity production per year and hectare.
788	
789	
790	

#### 791

#### Tables

792 Table 1. Main data and parameters from experimental analyses carried out on OFI.

Reference	Soil texture	Site	<b>Main annual rainfall</b> [mm yr <sup>-1</sup> ]	<b>Raw matter</b> [t ha <sup>-1</sup> yr <sup>-1</sup> ]	<b>Dry matter</b> [t ha <sup>-1</sup> yr <sup>-1</sup> ]	Mean rainfall-use efficiency factor (RUE) [kg ha <sup>-1</sup> yr <sup>-1</sup> mm <sup>-1</sup> ]	<b>BMP</b> [m <sup>3</sup> t <sup>-1</sup> DM <sup>-1</sup> ]	Biogas production [m <sup>3</sup> ha <sup>-1</sup> yr <sup>-1</sup> ]	CH₄ per cubic meter of biogas [%]	Electricity [kWh m <sup>-3</sup> ]	Electrical energy production [kWh ha <sup>-1</sup> yr <sup>-1</sup> ]
Santos et al. (2016)	Semi-arid	Alagoas, Pernambuco and Paraíba, Brazil	450*	89.7	7.9	18**	517	3717	60	1,25	4646
	Sandy	Argentina	300	N.A.	2.1 - 2.4	7.4	N.A.	N.A.	N.A.	N.A.	N.A.
Guevara & Estevez (2001)	Arid and sandy	Argentina	200 - 400	N.A.	3 - 9	15 - 22.5	N.A.	N.A.	N.A.	N.A.	N.A.
	Silty sand	Argentina	200	N.A.	0.75	3.5	N.A.	N.A.	N.A.	N.A.	N.A.
<b>Obach &amp; Lemus (2006)</b> cited by Santos et al. (2016)	N.A.	N.A.	N.A.	N.A.	300	N.A.	58ª	N.A.	52	1,5	23,400
Gasston et al. (2013) cited by Mason et al. (2015)	Sandy	Mutumayu, Kenya	500 - 600	120***	40	80 - 67 **	325	N.A.	N.A.	N.A.	53,200
De Cortázar &Nobel (1990)	Arid and semi-arid	Western South America	331	N.A.	32	97 **	N.A.	N.A.	N.A.	N.A.	N.A.
Comparetti et al. (2017)	Semi-arid	Sicily	300	N.A.	29**	97 **	300	770**	56**	0,109**	112**
Rosato (2014)	Semi-arid	Sicily	300	150**	12	40 **	350	3600**	60	N.A.	N.A.

\* Data acquired from https://it.climate-data.org/

\*\* Computed values from data

\*\*\* Computed average values for different planting densities

<sup>a</sup> Unit of measure: m<sup>3</sup> t<sup>-1</sup> SV<sup>-1</sup>

Table 2 – WGS84 geographical coordinates of the weather stations and related provinces

Meteorological station	Longitude	Latitude	Provinces of Sicily
Linguaglossa_Etna volcano	15.034649	37.790359	Catania
Ramacca	14.63355	37.48101	Catania
Caltagirone	14.57481	37.230025	Catania
Randazzo	14.97775	37.88973	Catania
Pedara	15.048439	37.642643	Catania
Paternò	14.855254	37.514767	Catania
Mineo	14.725331	37.319229	Catania
Mazzarrone	14.559542	37.096146	Catania
Maletto	14.872486	37.826202	Catania
Linguaglossa	15.130906	37.824482	Catania
Riposto	15.198342	37.685127	Catania
Catania	15.067711	37.441788	Catania
Adrano	14.833333	37.666667	Catania
Bronte	14.786194	37.753529	Catania
Gela	14.231500	37.081400	Caltanissetta
Aidone	14.446100	37.416500	Enna
Cesarò	14.713900	37.845800	Messina
Lentini	15.000400	37.286500	Syracuse
Montalbano Elicona	15.013500	38.025700	Messina
Agira	14.522400	37.657200	Enna
Comiso	14.611000	36.952400	Ragusa
Augusta	15.220500	37.237600	Syracuse
Antillo	14.245600	37.978300	Messina















209x296mm (300 x 300 DPI)