

Alma Mater Studiorum Università di Bologna
Archivio istituzionale della ricerca

On the power demands of accessories on an agricultural tractor

This is the final peer-reviewed author's accepted manuscript (postprint) of the following publication:

Published Version:

On the power demands of accessories on an agricultural tractor / Saetti M.; Mattetti M.; Varani M.; Lenzini N.; Molari G.. - In: BIOSYSTEMS ENGINEERING. - ISSN 1537-5110. - ELETTRONICO. - 206:(2021), pp. 109-122. [10.1016/j.biosystemseng.2021.03.015]

Availability:

This version is available at: <https://hdl.handle.net/11585/832183> since: 2022-10-17

Published:

DOI: <http://doi.org/10.1016/j.biosystemseng.2021.03.015>

Terms of use:

Some rights reserved. The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website.

This item was downloaded from IRIS Università di Bologna (<https://cris.unibo.it/>).
When citing, please refer to the published version.

(Article begins on next page)

This is the final peer-reviewed accepted manuscript of:

Matteo Saetti, Michele Mattetti, Massimiliano Varani, Nicola Lenzini, Giovanni Molari,
On the power demands of accessories on an agricultural tractor, in *Biosystems Engineering*, Volume 206, 2021, Pages 109-122, ISSN 1537-5110.

<https://www.sciencedirect.com/science/article/pii/S1537511021000763>

The final published version is available online at:

<https://doi.org/10.1016/j.biosystemseng.2021.03.015>

Rights / License:

The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website.

This item was downloaded from IRIS Università di Bologna (<https://cris.unibo.it/>)

When citing, please refer to the published version.

ON THE POWER DEMANDS OF ACCESSORIES ON AN AGRICULTURAL TRACTOR

Matteo Saetti^a, Michele Mattetti^{a*}, Massimiliano Varani^a, Nicola Lenzini^b, Giovanni Molari^a

^a Department of Agricultural and Food Sciences – Alma Mater Studiorum, Bologna University, viale G. Fanin, 50, 40127, Bologna, Italy

^b CNH Industrial – Tractor Innovation Engineering, viale delle Nazioni 55, 41100, Modena, Italy

*Michele Mattetti, DISTAL, University of Bologna, via G. Fanin 50, 40127 Bologna, Italy,
tel. +39 051 2096174, fax +39 051 2096178, email: michele.mattetti@unibo.it

ABSTRACT

Recently, the number of accessories in vehicle powertrains has been significantly increased. These accessories are necessary for vehicle operation. Accessories are driven by the engine, so their power demands result in a reduction of the vehicle's useful power. For heavy-duty vehicles, the most demanding accessories are the alternator; fan drive; heating, ventilation, and air-conditioning compressor, and brake air compressor. Their power demands vary according to the engine speed, and this may lead to notable energy losses especially in certain conditions, such as engine idling. This paper aims to evaluate the accessories power demands on a tractor equipped with an engine rating of 192 kW. In this tractor, a data logger together with auxiliary sensors were installed to monitor their power demands. During idling conditions, accessories power demands reach 38 % of the power provided by the engine and this leads to non-negligible impact on fuel consumption. The fuel consumption caused by accessories and their potential fuel savings by introducing electrically-driven accessories into tractor powertrains were estimated. A potential fuel saving of 232 l per year could be attained. This may lead to a yearly saving of 278 million litres of fuel and 747 thousand tons of CO₂ in the US. These savings were calculated assuming that all tractors are used with the same duty cycle. Even if it may not occur, thus the actual savings may be significantly different than that reported in this study, it permits to estimate if farming may benefit from tractors with electrically driven accessories.

32

33

34 **KEYWORDS:** engine accessories; powertrain; real-world data; fuel economy; vehicle

35 electrification.

Nomenclature	
β_{fan}	Estimate per cent fan speed
γ_{HVAC}	HVAC compressor engagement
ΔT	Temperature gradient between actual and setpoint cabin temperatures
Δt_{OC}	Total sampling period in generic operative condition
η_{alt}	Alternator efficiency
τ_{HVAC}	Transmission ratio between the engine angular speed and the HVAC compressor
τ_{alt}	Transmission ratio between the engine angular speed and the alternator
τ_{BAC}	Brake air compressor ratio
τ_{fan}	Transmission ratio between the engine angular speed and the fan drive
APU	Auxiliary power unit
D_{OC}	Duty cycle coefficient in generic operating condition
\bar{D}_{OC}	Average duty cycle coefficient in generic operating condition
ECU	Electronic control unit
$FC_{*,OC}$	Average fuel rate of a generic accessory (*) in generic operating condition
FR	Engine fuel rate
GNSS	Global navigation satellite system
HVAC	Heating, ventilation and air-conditioning
I_{alt}	Alternator output current
ICE	Internal combustion engine
$M_{eng\%}$	Actual engine percent torque
M_{er}	Engine reference torque
$M_{f\%}$	Nominal friction percent torque
N_{OC}	Number of samples in generic operating condition
n_{HVAC}	HVAC compressor speed
n_{alt}	Alternator speed
n_{BAC}	Brake air compressor speed
n_{eng}	Engine speed
n_{fan}	Fan speed
OC	Operating condition according to GNSS
$P_{*,OC}$	The average power demand of a generic accessory (*) in generic operating condition
P_{alt}	Alternator power demand
P_{atm}	Atmospheric pressure
P_{aux}	Total accessory power demand
$P_{aux,OC}$	Average accessory power demand in generic operating condition
P_{BAC}	Brake air compressor power demand
P_{eng}	Engine power
$P_{eng,OC}$	Average values of P_{eng} in generic operating condition
P_{fan}	Fan power demand
p_{filt}	Air filter pressure
P_{HVAC}	HVAC power demand
p_{in}	Air intake pressure
p_{tb}	Trailer brake compressor pressure
p_{tk}	Trailer brake tank pressure
PNG	Parameter number group
PTO	Power take-off
SPN	Suspect parameter number
RHP	Rear hitch position
S_{HVAC}	HVAC switch status
T_{cab}	Actual cabin temperature
T_{fan}	Engine coolant temperature
t_{OC}	Duration of the recorded data of each operating state
T_{sp}	Setpoint cabin temperature
t_{pc}	Pulse period of each cycle

t_{wc}	Pulse width of each cycle
v_a	Ground-based speed
V_{bat}	Battery potential

1. Introduction

Heavy-duty diesel vehicles, including agricultural tractors, produce relatively great amounts of nitrogen oxides (NO_x) and particulate matter (PM) compared with light-duty vehicles (Brodrick et al., 2002). Environmental concerns, fuel prices, and emissions regulations are pushing the engine industry to improve engine designs to reduce fuel consumption and emissions, so that modern society can lower the usage of fossil fuels. To this goal, research centres and vehicle manufacturers have been investigating the power demands of each component of powertrains. A family of components which has gained a lot of attention in recent years in heavy-duty vehicles are accessories (Baglione et al., 2007; Campbell & Kittelson, 2009). These are essential for ensuring the proper vehicle operation and operator comfort, but they limit the vehicle's useful power.

To meet driver expectations in terms of greater performance and comfort, the number and the size of accessories in vehicle powertrains have been increased in the last thirty years. Since they demand power to operate, their power losses are also taken into account in all engine drive cycle procedures (Hilliard & Springer, 1984). Among the others, the alternator; the fan drive; the heating, ventilation, and air-conditioning (HVAC) compressor and the brake air compressor are the most demanding accessories in heavy-duty vehicles (Hahn, 2008; Hendricks & O'Keefe, 2002).

On conventional tractors, accessories are belt-driven, which means they are driven by the engine through the serpentine belt, so their speeds are linearly dependent by the engine crankshaft speed. In this solution, accessories are controlled by the engine crankshaft speed and not by the parameter they control (e.g. engine coolant temperature for the fan drive). For this

reason, accessories are sized to meet performance requirements at a certain engine speed, and this may lead to two side effects (Campbell & Kittelson, 2009):

- **accessory overdrive:** when more power is delivered to an accessory than required by the function.
- **parasitic loading:** when accessories demand power even when no useful output is required.

These side effects lead to notable energy losses, especially in certain conditions such as engine idling (Andersson, 2004; Hnatzuk et al., 2000). In this engine status, the impact of accessories on engine fuel rate is large and a previous study reported a fuel rate increases up to 170 % when the HVAC compressor is engaged (Brodrick et al., 2002). Prolonged idle and high accessory loads are causes for great parasitic energy losses, which can be a non-marginal percentage of the delivered engine energy (Bass & Alfermann, 2003). Due to the above-mentioned side effects, accessories are designed to control a bit their operations in certain conditions, so their power demands can be reduced. For example:

- Alternators operate as a constant voltage source, so the delivered current is proportional to the voltage differential with the battery. However, their efficiencies are typically low (i.e. 60 %) (Perreault & Caliskan, 2004). Alternators do not include any strategy for reducing parasitic loading when the battery reaches the full state-of-charge. A feasibility study on controlling the engagement of the alternator with a magnetic clutch was carried out, and up to 6 % of fuel-saving with respect to a conventional system was observed (Sales, Sousa, Monteiro, & Rodrigues, 2018).
- The fan drives may integrate viscous couplings with ON/OFF or modulating behaviours (Pierce & Shepherd, 1982). The coupling is controlled by the engine management system (EMS), which controls the rotational speed of the fan as a function of the temperatures of engine coolant, lubricating oil, etc. (Buning, 2010; Lee et al., 2010).

With respect to conventional fan drives, viscous couplings permit to reduce the fuel rate up to 6 % and increase the useful engine power up to 10 % (Lee et al., 2011).

- The HVAC compressor can be disengaged through a magnetic clutch when the temperature requirement is met or when the evaporator temperature is below a certain value in order to prevent any HVAC damage (Shukla et al., 2018). The angular speed of the compressor determines the flow rate of the refrigerant that circulates in the system, and consequently, the heat transfer rate at the evaporator and condenser. The HVAC compressor demand is about 4 % of the power delivered by the engine (Hahn, 2008). Since the HVAC cooler typically operates in highly transient conditions due to the ON/OFF clutch control strategy, considerable energy saving was obtained by adopting supervisory energy management algorithms (Zhang et al., 2016).

- The brake air compressor is part of an open-loop circuit and it is controlled to maintain the pressure in the brake tank at a certain value. Thus, when no compressed air is needed, the air is released into the atmosphere, named as “idling state” in the following. This leads to an ON/OFF duty cycle, with prolonged circuit idling and significant energy losses (Buning, 2010).

Increases in fuel efficiency can be achieved by decoupling the accessories from the engine; thus, the impact of parasitic loadings and accessory overdrives can be reduced. This approach is not straightforward on conventional tractors, where the secondary energy source is the starting, lighting, and ignition battery, which is a low voltage electrical system, designed to power up to 1 kW of electricity (Emadi, Williamson, & Khaligh, 2006). Therefore, heavy-duty vehicle manufacturers have been investigating the potential fuel saving by adding different power supplies in vehicles, allowing them to take advantages of their different characteristics (Hamandi, Pèra, & Hissel, 2002). This is the principle of hybridisation, and two solutions have been investigated on heavy-duty vehicles: powering the accessories with auxiliary power units

(APUs) or replacing belt-driven accessories with electrically-driven ones. APUs are usually small diesel engines designed to power the accessories near their peak efficiencies. Thus, APUs are more efficient than the main engine at idle in powering the accessories. APUs are usually installed in heavy-duty trucks because these trucks are exposed to extremely prolonged idling periods for maintaining the battery voltage and the cab temperature at the desired levels when drivers sleep overnight inside the truck. APUs permit to run accessories even if the engine is turned off, and a study reported that APUs permit to reduce idling fuel rate up to 80 % with respect to belt-driven accessories (Lim, 2003).

Electrically-driven accessories are typically installed on hybrid vehicles, and they can be completely controlled on-demand, so they can be switched ON and OFF, or speed up and down (Moreda, Muñoz-García, & Barreiro, 2016). Even if part of the energy is lost for converting mechanical energy into an electrical energy, several studies report that moving from belt-driven accessories to electrically-driven ones permits to increase the fuel economy of vehicles in real operating conditions. The advantages are vehicle dependent, and in a minivan an increase of fuel economy up to 9.2 % was observed (Kluger & Harris, 2007), while on a hybrid bus a reduction in the accessory power demand up to 36 % was observed (Campbell & Kittelson, 2009). This difference is probably caused by the fact that buses require larger HVAC compressors than minivans. Considering that electrically-driven accessories could be run in function of the actual performance requirement, accessories and ICEs could be downsized, and this leads to a further lower fuel rate (Serrao et al., 2011).

The replacement of belt-driven accessories with electrically-driven ones seems to be the best practical way to reduce tractors' fuel consumption and emissions, but it may lead to more complicated powertrains. To design more efficient powertrains, a greater understanding of where the fuel energy is demanded is of utmost importance. Thus, fuel-saving potentials should be carefully evaluated on real-world data since the power demands of accessories are strongly

dependent on tractor operating conditions (Troncon et al., 2019). This data is not reported in any study.

This paper aims to quantify the power demands of the accessories in agricultural tractors under real-world operating conditions.

2. Materials and methods

The tests were carried out with a Steyr 6230 CVT tractor (CNH Industrial N.V., Amsterdam, NL) during its regular use. Its engine main specifications are reported in Table 1. Data were recorded for forty-five days at the Agricultural Farm of the University of Bologna (Cadriano, BO, Italy). In total, the tractor was used for 137 *h*, and during that time the tractor travelled for 1212 *km*.

Table 1 – Main specifications of the tractor engine		
Maximum engine power	(<i>kW</i>)	192
Number of cylinders	(–)	6
Engine tier	(–)	4B
Transmission	(–)	Continuously variable transmission
Battery	(<i>V</i>)	14

2.1 Accessories' specification

Accessories are located at the front of the tractor, fixed on the engine block, and they are driven by the engine through the serpentine belt.

The alternator is always engaged when the tractor is running, with a fixed transmission ratio. The alternator current varies in order to keep the battery at a fixed voltage, and it depends on the electrical loads. A voltage regulator controls the current distributed from the alternator to the battery in order to control the charging process.

The fan drive integrates a modulating viscous coupling which continuously controls the fan angular speed in function of the temperatures of engine coolant, transmission, and lubricating oils. The viscous coupling is controlled in a closed control loop with a PID controller which

limits the temperature to set-point values. The PID governor can control the transmission ratio between the engine crankshaft and the fan (τ_{fan}) in the range between 0.75 (maximum modulation) and 1.25 (minimum modulation).

The HVAC compressor is a constant displacement compressor with a magnetic clutch controlled by the HVAC controller to realise a variable cooling capacity. The cooling requirement inside the cab is sensed by a thermistor that sends a signal to the HVAC controller, which controls the engagement of the magnetic clutch in order to meet the cooling requirement of the driver. Moreover, the HVAC controller disengages the clutch when the evaporator temperature is below 3 °C, and it reengages the clutch when the temperature rises above 5 °C in order to prevent any damage of the evaporator. Moreover, the driver can operate directly on a switch placed into the cabin, choosing between four different configurations: one automatic state, and three manual states with three different blower speeds. On automatic state, the compressor can vary the mass flow rate of the refrigerant and the cooling requirement in order to meet the temperature set-point controlled by the driver (Shukla et al., 2018). Fig. 1 shows the HVAC compressor in the tractor architecture.

Fig. 1:

The brake air compressor is integrated into a circuit with a feedback signal coming from a pressure transducer on the tank. When the tank pressure is below 7 bar, the compressor works to add air to the tanks, otherwise the compressor releases air into the atmosphere.

2.2 Acquisition system – CAN-Bus data logger

The test was carried out according to the approach introduced by Molari et al. (2013). Tractor CAN-Bus data were recorded through a stand-alone CAN-Bus data-logger optimized by CNH Industrial. The CAN-Bus data logger automatically recorded all the CAN-Bus messages

anytime the tractor engine was turned on; thus, data were collected in totally uncontrolled conditions in order to not interfere with any farming activities.

Auxiliary sensors were connected to the CAN-Bus data-logger to record information which was not otherwise available into the CAN-Bus network. In particular:

- Alternator output current (I_{alt}): measured with a current sensor (HTA200S, LEM GmbH, Europe) placed in the positive terminal of the alternator (Fig. 2).
- Trailer brake compressor pressure (p_{tb}): measured with a pressure sensor (PX3AG1BH010BSAAX, Honeywell International Inc., Europe) placed in the compressor head (Fig. 3).
- Air intake pressure (p_{in}): measured with a pressure sensor (PX3AG1BH010BSAAX, Honeywell International Inc., Europe) placed at the compressor inlet.
- Trailer brake tank pressure (p_{tk}): measured with a pressure sensor (PX3AG1BH010BSAAX, Honeywell International Inc., Europe) placed in the compressor tank.

Each auxiliary sensor was connected to the CAN-Bus data logger through a CSM ADMM pro 2 (CSM GmbH, Filderstadt, Germany), which is a CAN-Bus interface for analogue signals.

Fig. 2

Fig. 3

For the purpose of this study, the CAN-Bus signals with the Suspect Parameter Numbers (SPNs) and Parameter Group Numbers (PGNs) (ISO, 2012; SAE, 2013) reported in Table 2 were used for the analysis.

Table 2 – Signal identifications					
Name	SPN	PNG	Definition	Id.	Unit
Engine speed	190	61444	Revolution speed of the engine crankshaft	n_{eng}	rpm
Ground-based speed	1859	65097	Actual ground speed of the tractor	v_a	$m\ s^{-1}$
Battery potential	168	65271	Battery voltage	V_{bat}	V
Engine reference torque	544	65251	Peak torque used as a reference value for all indicated engine torque parameters	M_{er}	$N\ m$
Actual engine percent torque	513	61444	Engine torque as a per cent of reference engine torque. The value includes the torque developed in the cylinders required to overcome friction	$M_{eng\%}$	[-]
Nominal friction-percent torque	514	5398	Torque contribution of frictional and thermodynamic losses of the engine itself, pumping torque loss and the losses of fuel, oil, and cooling pumps	$M_{f\%}$	[-]
Fan speed	1639	65213	Revolution speed of the fan associated with the engine coolant system	n_{fan}	rpm
Estimate percent fan speed	975	65213	The ratio of the fan drive (current speed) to the fully engaged fan drive (maximum fan speed)	β_{fan}	[-]
Engine coolant temperature	110	65262	The temperature of the liquid in engine the engine cooling system	T_{fan}	[-]
HVAC compressor engagement	1351	65198	Engagement of the air compressor: 0 when the compressor is engaged, and 1 when the compressor is disengaged	γ_{HVAC}	[-]
HVAC switch status	7853	64993	State of the control switch inside the cab. There is an automatic airflow ratio modulation state, and three fixed airflow rate levels named as “Speed1”, “Speed2”, and “Speed3” hereafter	S_{HVAC}	[-]
Actual cabin temperature	170	65269	The temperature inside the cab	T_{cab}	$^{\circ}C$
Setpoint cabin temperature	1691	57344	Temperature set by the operator in the cab	T_{sp}	$^{\circ}C$
Engine fuel rate	183	65266	Amount of fuel consumed per unit of time	FR	$l\ h^{-1}$

201

202 All the data recorded when the tractor was run for less than 300 s in a day were excluded

203 from the analysis, which could be caused by a non-operational use of the tractor, such as

204 downloading data from the CAN-Bus data-logger. The recorded signals were interpolated at
205 0.1 s through a spline interpolation algorithm.

206 2.3 Signal post-processing

207 The engine power (P_{eng}) was calculated with the equation (1):

$$P_{eng} = \left(\frac{2 \pi n_{eng}}{60} \right) \cdot M_{er} \cdot \frac{(M_{eng\%} - M_{f\%})}{100} \quad (1)$$

208

209 The alternator power demand (P_{alt}) was calculated with the equation (2):

$$P_{alt} = \frac{(V_b \cdot I_{alt})}{\eta_{alt}} \quad (2)$$

210 η_{alt} being the alternator efficiency and it was calculated with equation (3):

$$\eta_{alt} = a_{alt} + b_{alt} n_{alt} + c_{alt} n_{alt}^2 + d_{alt} n_{alt}^3 \quad (3)$$

211 a_{alt} , b_{alt} , c_{alt} and d_{alt} being regression coefficients calculated by fitting the efficiency curve
212 of the alternator (provided by the manufacturer). n_{alt} is the alternator angular speed and it was
213 calculated with equation (4):

$$n_{alt} = n_{eng} \tau_{alt} \quad (4)$$

214 τ_{alt} being the transmission ratio between the engine crankshaft, and the alternator shaft.

215 The fan power demand (P_{fan}) was calculated with the equation (5):

$$P_{fan} = a_{fan} n_{fan} + b_{fan} n_{fan}^2 + c_{fan} n_{fan}^3 \quad (5)$$

216 a_{fan} , b_{fan} and c_{fan} being regression coefficients calculated from test bench data. n_{fan} is the
217 fan angular speed.

218 The HVAC compressor power demand (P_{HVAC}) is dependent on refrigerant charge level,
219 blower speed, actual ambient temperature, and compressor speed; however, the compressor

220 speed is much more influential than the others (Joudi et al., 2003; Macagnan et al., 2013). To
 221 limit the number of sensors to install in the tractor, a pragmatic approach was adopted in this
 222 study, where P_{HVAC} was calculated with the equation (6), considering only the HVAC
 223 compressor speed (n_{HVAC}) (Zhong, 2018), and γ_{HVAC} :

$$P_{HVAC} = (a_{HVAC} + b_{HVAC} n_{HVAC} + c_{HVAC} n_{HVAC}^2) \gamma_{HVAC} \quad (6)$$

224 a_{HVAC} , b_{HVAC} , and c_{HVAC} being regression coefficients calculated from test bench data. n_{HVAC}
 225 the HVAC compressor angular speed and it was calculated with equation (7):

$$n_{HVAC} = n_{eng} \tau_{HVAC} \quad (7)$$

226 τ_{HVAC} the transmission ratio between the engine crankshaft and the HVAC compressor pulley.

227 The brake air compressor power (P_{BAC}) is dependent by the compressor outlet flow rate,
 228 which in turn depends on its swept volume (V_{BAC}), and its angular speed (n_{BAC}); the inlet
 229 pressure on the air intake manifold (p_{in}); and, finally, the compressor outlet pressure ($p_{tb} +$
 230 p_{atm}), where p_{atm} is the atmospheric pressure. Considering an adiabatic process, P_{BAC} was
 231 calculated with the formula (8):

$$P_{BAC} = n_{BAC} \frac{k}{k-1} p_{in} V_{BAC} \left[\left(\frac{p_{tb} + p_{atm}}{p_{in}} \right)^{\frac{k-1}{k}} - 1 \right] \frac{1}{\eta_{BAC}} \quad (8)$$

232 k being the heat capacity ratio and η_{BAC} being the compressor efficiency. n_{BAC} was calculated
 233 with equation (9):

$$n_{BAC} = n_{eng} \tau_{BAC} \quad (9)$$

234 τ_{BAC} being the transmission ration between the engine crankshaft and the pulley of the brake
 235 air compressor. The brake air compressor operates in idle state when p_{tb} is lower than 0.1 bar,
 236 otherwise it operates in the load state.

237

In Fig. 4, the characteristic curve of each accessory is reported as a function of n_{eng} . The fan drive, and the alternator can operate on an area due to their embedded load control strategies. In particular, for the alternator, the area is given by a set of constant voltage curves, where the upper boundary curve was obtained with a voltage differential of 13 V ($\pm 0.5\%$). For the fan drive, the area where the fan operates is limited by the two extreme values of τ_{fan} . On the other hand, the HVAC compressor runs on a characteristic curve according to n_{eng} , and the brake air compressor runs on the two different characteristics curves.

Fig. 4

The total accessory power demand (P_{aux}) was calculated with equation (10):

$$P_{aux} = P_{alt} + P_{fan} + P_{HVAC} + P_{BAC} \quad (10)$$

Since the power losses of the tractor are strongly dependent on the operating conditions (OCs), the recorded data were classified according to the classification scheme developed by Mattetti et al. (2020). In this classification scheme, three different operating conditions were introduced:

- *idle*: standing tractor with no use of both PTOs, and with $n_{eng} < 850 \text{ rpm}$.
- *moving*: moving tractor with no use of PTOs, and three-point linkages.
- *field work*: tractor operating on the field when a repetitive pattern of a pass, headland turn and pass was observed.

In Fig. 5, a portion of the P_{eng} signal classified with the before mentioned tractor classifications is reported.

Fig. 5

For each operating condition, the average values of all the above-mentioned signals were calculated. All these values will be denoted with the subscript OC (e.g., $P_{eng,OC}$ denotes the average values of P_{eng} in a generic operating condition). For intermittently used accessories, which are the HVAC and the brake air compressor, their duty cycles for each operating condition (D_{OC}) were calculated with the equation (11):

$$D_{OC} = \frac{t_{wc}}{t_{pc}} \quad (11)$$

t_{pc} being the pulse period of each cycle, t_{wc} being the pulse width of each cycle and different operating conditions (Fig. 6).

Fig. 6

The average duty cycle (\bar{D}_{OC}) was calculated for each operating condition with the equation (12):

$$\bar{D}_{OC} = \frac{1}{N_{OC}} \sum_{i=1}^{N_{OC}} D_{OC,i} \quad (12)$$

being N_{OC} the number of cycles of each operating condition.

Finally, for each operating condition, the fuel consumed by each accessory ($FC_{*,OC}$) was calculated with equation (13):

$$FC_{*,OC} = \frac{P_{*,OC}}{P_{eng}} \int_0^{t_{oc}} FR_{OC} \cdot dt \quad (13)$$

t_{oc} being the duration of the recorded data during each operating condition, $FR_{*,oc}$ and $P_{*,oc}$ being the engine power and fuel rate for each operating condition, respectively. The asterisk in the subscript standing for the consumed fuel or power of a generic accessory.

3. Results and discussion

The discussion will start by reporting the behaviour of each accessory, and then their contribution to engine power demands and fuel consumption will be reported.

3.1 Alternator

In Fig. 7 – left, the joint probability distribution between I_{alt} and V_{bat} is reported. Indeed, a mild negative correlation can be observed between I_{alt} and V_{bat} (the Pearson's correlation coefficient is -0.52). That is because the alternator is designed to operate as a constant voltage source, so the higher the voltage differential is between the battery and the alternator, the greater is I_{alt} . I_{alt} is strongly dependent on the electrical load which in case of the tractor under study is mostly caused by the lights, the blower fan of the HVAC, and the radio. The voltage supplied by the alternator is such as to allow V_{bat} to range between 13.5 and 13.8 V. The distribution has a single mode, which is located at 13.6 V and 38.5 A, which occurred 10.5 % of the time. In Fig. 7 – right, the joint probability distribution between P_{alt} and n_{eng} is reported. However, P_{alt} is function of n_{alt} , which in turn depends on n_{eng} , so P_{alt} is poorly correlated with n_{eng} (the Pearson's correlation coefficient is 0.36). This is due by the fact that I_{alt} mostly depends on the electrical load demand and battery-state-of-charge, and both are independent on n_{eng} . The joint probability distribution has a trend that leads back to the alternator characteristic curve (Fig. 4), but much lower values of P_{alt} were recorded due to the greater state of charge of the battery. Indeed, the maximum value of P_{alt} is 1.5 kW, but the alternator could generate up to 5 kW (Fig. 4). On average, P_{alt} on idle is lower than P_{alt} on greater n_{eng} ; indeed, the two major

peaks of the distribution, located at 875 *rpm* and 2053 *rpm* occur at 0.7 *kW* and 0.9 *kW*, respectively (Fig. 7 – right). This is caused by the fact that the engine mostly operates at the idling speed and at the speed where the maximum power occurs.

Fig. 7

3.2 Fan drive

In Fig. 8 – left, the joint probability distribution between n_{fan} and n_{eng} is reported. The upper and bottom boundaries of the distribution represent the two extreme operating conditions with minimum and maximum fan drive modulation, respectively. The area between the two boundaries represents the points where intermediate fan drive modulations occurred. One can note that the engine idle condition with minimum modulation is the point where the joint probability is the highest. That is because, differently from the other operating conditions, idling occurs at a specific n_{eng} . All the modes of the distribution are located along the minimum modulation boundary at 800 *rpm*, 1350 *rpm*, and 2050 *rpm*. In Fig. 8 – right, the joint probability distribution between T_{fan} and n_{eng} is reported. The distribution resembles a typical shape of a viscous coupling (Buchholz, 2005). Indeed, when T_{fan} was below 80 °C, the fan drive runs at around 1000 *rpm* (i.e., fan drive idling speed) for reducing the fuel rate. When T_{fan} rose above 80 °C, the fan drive was activated, and n_{fan} was increased. In the vertical band of the distribution, the ECU controls the fan drive behaviour, and the width of this band permits to quantify the system hysteresis, which is about 10 °C (considering only the point where the higher probability occurs), and this amount is aligned to that reported in other studies (Pierce & Shepherd, 1982). Fan drive hysteresis is necessary to prevent high switching frequency which may results in damage of the viscous coupling. T_{fan} ranges from 30 °C (i.e. ambient

temperature) to 105 °C (which is close to the engine coolant warning limit). In the distribution, two major modes can be distinguished, located at 1076 rpm, and 1700 rpm of n_{fan} .

Fig. 8

The time percentage of β_{fan} , divided into its three main use configurations:

- maximum modulation when $\beta_{fan} = 0$;
- intermediate modulation when $0 < \beta_{fan} < 1$;
- minimum modulation when $\beta_{fan} = 1$.

The fan drive worked at minimum modulation condition for 49% of the time and at intermediate modulation condition for 45%. Moreover, the fan drive worked at maximum modulation state only for 9% of the time, and especially only for short transitional periods, during the cold-start and warm-up phases, probably because the measurements were carried out in the summertime, which is the period of the year where this type of tractor is mostly used.

In Fig. 9, the joint probability distribution between P_{fan} and P_{eng} is reported. Even if the heat generated by a combustion engine is proportional to the engine power (Ferrari, 2016), P_{fan} is not correlated with P_{eng} (Pearson's correlation coefficient is 0.29). This is due to the fact that viscous coupling is handled by few temperature signals and not by the engine operating point. In certain conditions (i.e., engine idling), this may lead to an unwanted early cooling with a decrease of engine efficiency due to large heat exchange (Haghighat et al., 2018). The distribution shows an increasing trend of the P_{fan} with respect to engine load, up to 11.5 kW when P_{eng} is greater than 160.0 kW. The lowest value of P_{fan} is 0.2 kW, during the ignition phases.

Fig. 9

3.3 HVAC compressor

In Fig. 10, portions of S_{HVAC} , γ_{HVAC} , t_{cab} , and P_{HVAC} signals are reported. From the analysis of the signals' behaviours, it can be noted that when the switch is on "Auto" and the difference between T_{cab} and T_{sp} (named ΔT hereafter) is lower than 5°C , it leads to a cycling clutch operation, which causes oscillations in P_{HVAC} . Cyclic fluctuations are quite frequent even during HVAC manual states (i.e. "Speed 1", "Speed 2", and "Speed 3" settings), where the blower speed is fixed and the HVAC compressor does not vary the cooling capacity.

Fig. 10

During the test period, the HVAC compressor was engaged for 82.5 % of the time, of which: 61 % on "Auto" state, 4 % on "Speed 1" state, 17 % on "Speed 2", and 0.5 % on "Speed 3" state. The prolonged use of the HVAC compressor is caused by the high temperature recorded in the period of the test. Indeed, T_{cab} ranged from 18.6°C to 43.3°C ; in particular, for 25 % of the time, Δt was lower than 5°C .

In Table 3, the average values of tp_c and D_{OC} are reported. For both automatic and manual states, tp_c is approximately the same, at around 120 s. However, on manual states, the HVAC was engaged longer than the automatic state, since D_{OC} on manual states is higher than the automatic state: this is probably since on manual states the ΔT was on average 10.1°C , and on automatic states Δt was on average 7.7°C .

Table 3 – Average parameters of HVAC compressor duty cycle for the operating conditions
* Automatic state; ** Manual states.

OC	tp_i [s]	D_i [%]
Idle	120*/118**	53*/70**
Moving	136*/135**	54*/65**
Field work	137*/114**	63*/71**

3.4 Brake air compressor

In Fig. 11, a portion of the p_{tb} , p_{tk} , and P_{BAC} signals are reported. For the compressor, an ON/OFF duty cycle can be observed. When p_{tk} drops below 7 bar, the compressor is in the load state and p_{tb} rises from 0.2 bar to 10.8 bar. Similarly, P_{BAC} varies in function of the circuit load state and n_{BAC} (see formula (8)). Indeed, the peak values of P_{BAC} in idling and loading states are 0.1 kW and 2.9 kW, respectively. When the brake air compressor is on idling, it does not produce any useful work. The higher n_{BAC} is and the higher the air flow rate provided by the brake compressor is, the lower the time required for refilling the tank is.

Fig. 11

The brake air compressor operated in the idle state for 98 % of the time, and in Fig. 11, its intermittent behaviour is highlighted. In Table 4, the average values of tp_c and D_{OC} are reported. Every few minutes, the brake air compressor switches into a load state and is in this state for around a minute. The frequency of the switching state of the brake air compressor should be dependent on the air losses inside the tank, and on frequency of actuation of trailer brake. However, this effect was not observed during the test.

Table 4 – Average parameters of brake air compressor duty cycle for the operating conditions

<i>OC</i>	<i>tp_i</i> [s]	<i>D_i</i> [%]
Idle	130	38
Moving	187	29
Field work	236	38

3.5 Comparative analysis of accessories power demand

In Table 5, for each tractor operating condition, the time contribution and the average values of n_{eng} and P_{eng} are reported. The tractor operated most of the time (i.e., 66 %) for field work

operating conditions. Thanks to the data coming to beacon scanner, the tractor operated for 49% of time with a plough, for 33% of time with a cultivator and for 11% of time with a trailer. In the rest of time the tractor operated without any implement, mostly for road transportation.

In this operating condition, much greater values of the average value of $P_{eng,OC}$ than those of the other operating conditions were observed. Even if the average value of $P_{eng,OC}$ during moving condition is 57% of that of the field work, the average value of $P_{aux,OC}$ during moving conditions is 88% of that of the field work operating condition. This is mostly because the two operating conditions lead to a similar average value of $n_{eng,OC}$. However, in terms of percentage, the average value of $P_{aux,OC}$ is the greatest during the idling operating condition, since the engine does not produce any useful work and most of the power from the engine is used for overcoming the engine losses (i.e., friction, thermodynamic, pumping losses, etc.) and accessory loads. During field work operating conditions, the greatest $P_{eng,OC}$ was observed, and the contribution of $P_{aux,OC}$ with respect to $P_{eng,OC}$ is only 14%.

Table 5 – Average values for each defined operating condition

* percentages of $P_{aux,OC}$ were calculated with respect to P_{eng}

OC	$Time_{OC}$ [%]	$n_{e,OC}$ [rpm]	$P_{eng,OC}$ [kW]	$P_{aux,OC}$ [kW/%*]
Idle	16	853	10.4	4.0/38.5
Moving	18	1444	65.0	14.5/22.3
Field work	66	1573	114.8	15.7/13.7

The histogram of Fig. 12– left reports the average power demand of each accessory during each operating condition. Each operating condition leads to a different engine operating point and consequently to a different accessory power demand. The HVAC compressor and the fan drive are the accessories with the greater power demands in any operating condition, while the alternator and the brake compressor are by far less demanding. During the engine idling, the HVAC compressor is the most demanding accessory, while in all the others, the fan drive is the most demanding. Indeed, when n_{eng} is lower than 1300 rpm, P_{HVAC} is greater than P_{fan} (Fig.

408 4). The power demand of the brake air compressor is in any condition the lowest, even if it
409 could reach significant peak values (Fig. 4). That is because the brake air compressor was in
410 idle over prolonged periods, and this reduces the average value of its power demand.

411 The results reported in this paper can be compared with other types of heavy-duty vehicles,
412 long haulage trucks and city buses, where their accessory power demands are around 5 – 7 %,
413 respectively (Sjostedt et al., 2014). This great difference is probably caused by the fact that the
414 cooling fan provides the major contribution to engine heat controls due to the lower ground
415 speed of agricultural tractors than on-road vehicles. Considering that tractors of this class are
416 used up to 850 hours per year (Mattetti, Maraldi, et al., 2019), a total of 18613 l of fuel were
417 consumed. Of that, 15.4 % were consumed for accessories. In Fig 12 – right. the yearly fuel
418 consumption caused by each accessory and each operating condition are reported. Most of the
419 fuel is consumed during the field work operating state by the fan drive and the HVAC
420 compressor, while the alternator and the brake air compressor are responsible for only 2.1 % of
421 the total fuel consumption.

422
423 *Fig. 12*
424

425 **4. Conclusions**

426 The current agricultural market trend is pushing tractor manufactures and research centres
427 to investigate hybrid configurations in order to increase tractor fuel efficiency. In the last
428 decades, research and manufacturers mostly focused on engine combustion efficiency, but more
429 recently, efforts have been made to investigating on the efficiency of all power demands in
430 powertrains. On tractors, a non-negligible part of the power is absorbed by accessories due to
431 their size. However, their operational requirements are different than the nominal and no studies

had quantified the amount of fuel consumed by the accessories and their environmental impact on the real operating condition. In the period under study, the tractor consumed 462 l of fuel only for the accessories. Tractors of this class are used up to 850 hours per year, so accessories are responsible for yearly fuel consumption of 2866 l. This consumption can be reduced by equipping tractors with electrically-driven accessories, which can be turned off when they are not needed. For example, an electrical brake air compressor can be turned off when the brake air tank is full, and in that case, a yearly fuel savings of 34.3 l could be achieved. Electrically-driven accessories can also be run with the engine off. This is especially useful for reducing the need for unnecessary idling, which is accounted for 67% of the entire idling (Molari et al., 2019). In that case, it is expected to save 216 l of fuel every year. The total benefit will be a fuel savings of 232 l, which is 8.1% of the entire fuel consumed for accessories. Even though this amount seems to be negligible, one should consider that 1.2 million of tractors of this class, in terms of engine power, are in use in the U.S. (Perdue & Hamer, 2019), and thus a fuel savings of 278 million litres could be obtained per year, which would lead to a reduction of CO₂ emissions of about 747 thousand tons per year (2.69 kg of CO₂ per litre of diesel fuel was used of conversion factor). This can lead to a significant improvement in tackling climate change. The estimated savings were calculated assuming that all tractors are used with the same duty cycle, but this may not occur. So, the actual savings may be significantly different than those reported in this study. However, this study is the first comprehensive study on tractor accessories and the first one that attempted to quantify the potential fuel savings caused by the electrification of accessories. This figure will permit to evaluate if farming may benefit from tractors with electrically driven accessories.

In the coming years, researchers and tractor manufacturers should think of novel solutions for accessories which permit to increase the tractor fuel efficiency and to add new functionalities, otherwise farmers could perceive electrically-driven accessories as solutions

which lead to the higher purchasing price. Future research will be required to investigate the power losses and fuel-saving, with related emissions, in tractors with hybrid powertrains, to compare their efficiency. In addition, the use of dedicated equipment to accurately assess the energy demand of accessories: for example, heat meter can be installed to measure the heat exchange and the real demand of HVAC compressor.

Acknowledgements

This project was supported by PRIN (Research projects of significant national interest) notification 2017 “*Green SEED: Design of more-electric tractors for a more sustainable agriculture*”, grant number: 2017SW5MRC.

REFERENCES

- 466 Andersson, C. (2004). *On Auxiliary Systems in Commercial Vehicles* [Doctoral Dissertation in
467 Industrial Electrical Engineering]. Lund University.
- 468 Baglione, M., Duty, M., & Pannone, G. (2007). Vehicle System Energy Analysis Methodology
469 and Tool for Determining Vehicle Subsystem Energy Supply and Demand (SAE
470 Technical Paper N. 2007-01-0398). SAE International. [https://doi.org/10.4271/2007-](https://doi.org/10.4271/2007-01-0398)
471 01-0398
- 472 Bass, E., & Alfermann, T. (2003). The Influence of Idle, Drive Cycle and Accessories on the
473 Fuel Economy of Urban Hybrid Electric Buses—Chassis Dynamometer Tests. *SAE*
474 *Technical Paper*, 2003-01-3438. <https://doi.org/10.4271/2003-01-3438>
- 475 Brodrick, C.-J., Dwyer, H. A., Farshchi, M., Harris, D. B., & Jr, F. G. K. (2002). Effects of
476 Engine Speed and Accessory Load on Idling Emissions from Heavy-Duty Diesel Truck
477 Engines. *Journal of the Air & Waste Management Association*, 52(9), 1026–1031.
478 <https://doi.org/10.1080/10473289.2002.10470838>
- 479 Buchholz, T. (2005). *Engine cooling fan control system* (United States Patent No.
480 US6894883B2). <https://patents.google.com/patent/US6894883B2/en>
- 481 Bunning, E. A. (2010). Electric drives in agricultural machinery — Approach from the tractor
482 side. Club of Bologna, 1–13.
483 https://www.clubofbologna.org/ew/ew_proceedings/KNR_Buning.pdf
- 484 Campbell, J., & Kittelson, D. (2009). Superbus Phase I: Accessory Loads Onboard a Parallel
485 Hybrid- Electric City Bus. *University of Minnesota Center for Transportation Studies*.
486 <http://conservancy.umn.edu/handle/11299/97663>

487 Emadi, A., Williamson, S. S., & Khaligh, A. (2006). Power electronics intensive solutions for
 488 advanced electric, hybrid electric, and fuel cell vehicular power systems. *IEEE*
 489 *Transactions on Power Electronics*, 21(3), 567–577.
 490 <https://doi.org/10.1109/TPEL.2006.872378>

491 Ferrari, G. (2016). Internal combustion engine. *Società editrice Esculapio*.

492 Haghighat, A. K., Roumi, S., Madani, N., Bahmanpour, D., & Olsen, M. G. (2018). An
 493 intelligent cooling system and control model for improved engine thermal management.
 494 *Applied Thermal Engineering*, 128, 253–263.
 495 <https://doi.org/10.1016/j.applthermaleng.2017.08.102>

496 Hahn, K. (2008). High Voltage Electric Tractor-Implement Interface. *SAE International*
 497 *Journal of Commercial Vehicles*, 1(1), 383–391. <https://doi.org/10.4271/2008-01-2660>

498 Hamandi, S., Péra, M. C., & Hissel, D. (2002). Fuel Cell Systems for Electrical Vehicles:
 499 Solutions, Modelling and Test benches design.
 500 [https://www.researchgate.net/publication/229040000_Fuel_Cell_Systems_for_Electric](https://www.researchgate.net/publication/229040000_Fuel_Cell_Systems_for_Electrical_Vehicles_Solutions_Modelling_and_Test_benches_design)
 501 [al_Vehicles_Solutions_Modelling_and_Test_benches_design](https://www.researchgate.net/publication/229040000_Fuel_Cell_Systems_for_Electrical_Vehicles_Solutions_Modelling_and_Test_benches_design)

502 Hendricks, T., & O’Keefe, M. (2002). Heavy Vehicle Auxiliary Load Electrification for the
 503 Essential Power System Program: Benefits, Tradeoffs, and Remaining Challenges. *SAE*
 504 *Technical Paper*, 2002-01–3135. <https://doi.org/10.4271/2002-01-3135>

505 Hilliard, J. C., & Springer, G. S. (1984). *Fuel Economy*. Springer US.
 506 <https://doi.org/10.1007/978-1-4899-2277-9>

507 Hnatzuk, W., Lasecki, M. P., Bishop, J., & Goodell, J. (2000). Parasitic Loss Reduction for
 508 21st Century Trucks. *SAE Technical Paper*, 2000-01–3423.
 509 <https://doi.org/10.4271/2000-01-3423>

510 ISO. (2012). *ISO 11783-7:2012—Tractors and machinery for agriculture and forestry—Serial*
 511 *control and communications data network—Part7: Implement messages application*
 512 *layer—Implement messages application layer.*

513 Joudi, K. A., Mohammed, A. S. K., & Aljanabi, M. K. (2003). Experimental and computer
 514 performance study of an automotive air conditioning system with alternative
 515 refrigerants. *Energy Conversion and Management*, 44(18), 2959–2976.
 516 [https://doi.org/10.1016/S0196-8904\(03\)00051-7](https://doi.org/10.1016/S0196-8904(03)00051-7)

517 Kluger, M., & Harris, J. (2007). Fuel Economy Benefits of Electric and Hydraulic Off Engine
 518 Accessories. *SAE Technical Paper*, 2007-01–0268. [https://doi.org/10.4271/2007-01-](https://doi.org/10.4271/2007-01-0268)
 519 [0268](https://doi.org/10.4271/2007-01-0268)

520 Lee, M. H., Kim, M. K., Park, H. G., Lee, K. S., & Chun, H. H. (2011). Electronically controlled
 521 viscous cooling fan clutch in the vehicle. *International Journal of Precision*
 522 *Engineering and Manufacturing*, 12(6), 983–992. [https://doi.org/10.1007/s12541-011-](https://doi.org/10.1007/s12541-011-0131-7)
 523 [0131-7](https://doi.org/10.1007/s12541-011-0131-7)

524 Lee, M. H., Lee, W. B., Lee, J. H., Koh, Y. H., Park, J. H., & Harashima, F. (2010). On the
 525 Cooling Fan Actuator to EMS in the Vehicle. *Journal of Mechanical Systems for*
 526 *Transportation and Logistics*, 3(3), 521–536. <https://doi.org/10.1299/jmtl.3.521>

527 Lim, H. (2003). Study of Exhaust Emissions from Idling Heavy Duty Diesel Trucks and
 528 Commercially Available Idle Reducing Devices. *SAE Technical Paper*, 2003-01–0288.
 529 <https://doi.org/10.4271/2003-01-0288>

530 Macagnan, M., Coppetti, J., De Souza, R., Reichert, R., & Amaro, M. (2013). Analysis of the
 531 influence of refrigerant change and compressor duty cycle in an automotive air
 532 conditioning system. *COBEM 2013. 22nd International Congress of Mechanical*
 533 *Engineering, Ribeirão Preto, SP, Brazil.*

534 Mattetti, M., Maraldi, M., Lenzini, N., Fiorati, S., Sereni, E., & Molari, G. (2021). Outlining
 535 the mission profile of agricultural tractors through CAN-BUS data analytics. *Computers*
 536 *and Electronics in Agriculture*, 184, 106078.
 537 <https://doi.org/10.1016/j.compag.2021.106078>
 538 Mattetti, Michele, Maraldi, M., Sedoni, E., & Molari, G. (2019). Optimal criteria for durability
 539 test of stepped transmissions of agricultural tractors. *Biosystems Engineering*, 178, 145–
 540 155. <https://doi.org/10.1016/j.biosystemseng.2018.11.014>
 541 Molari, G., Mattetti, M., Lenzini, N., & Fiorati, S. (2019). An updated methodology to analyse
 542 the idling of agricultural tractors. *Biosystems Engineering*, 187, 160–170.
 543 <https://doi.org/10.1016/j.biosystemseng.2019.09.001>
 544 Molari, G., Mattetti, M., Perozzi, D., & Sereni, E. (2013). Monitoring of the tractor working
 545 parameters from the CAN-Bus. *Journal of Agricultural Engineering*, 44(2s).
 546 <https://doi.org/10.4081/jae.2013.319>
 547 Moreda, G. P., Muñoz-García, M. A., & Barreiro, P. (2016). High voltage electrification of
 548 tractor and agricultural machinery – A review. *Energy Conversion and Management*,
 549 115, 117–131. <https://doi.org/10.1016/j.enconman.2016.02.018>
 550 Perdue, S., & Hamer, H. (2019). *Census of Agriculture: United States summary and State data*.
 551 United States Department of Agriculture.
 552 Perreault, D. J., & Caliskan, V. (2004). Automotive Power Generation and Control. *IEEE*
 553 *Transactions on Power Electronics*, 19(3), 618–630.
 554 <https://doi.org/10.1109/TPEL.2004.826432>
 555 Pierce, S. M., & Shepherd, M. (1982). Development of a Modulating Viscous Fan Drive for
 556 Agricultural Tractors. SAE Technical Paper, 1982-02-01.
 557 <https://doi.org/10.4271/821043>

558 SAE. (2016). J1939/71—Vehicle Application Layer (J1939/71_201610; Ground Vehicle
559 Standard). https://saemobilus.sae.org/content/j1939/71_201610

560 Sales, L. C. M., Sousa, J. M. S., Monteiro, L. G. C., Rodrigues, J. P., & Borges, F. R. (2018).
561 Experimental comparative analysis of the combined Stop & Start and alternator with
562 mechanical decoupling strategies. *SAE Technical Paper*, 2018-36-0341.
563 <https://doi.org/10.4271/2018-36-0341>

564 Serrao, L., Onori, S., & Rizzoni, G. (2011). A Comparative Analysis of Energy Management
565 Strategies for Hybrid Electric Vehicles. *Journal of Dynamic Systems, Measurement, and*
566 *Control*, 133(3), 031012. <https://doi.org/10.1115/1.4003267>

567 Shukla, A. K., Bhargava, A., Sachin, K. S., & Jain, R. (2018). Development and Optimization
568 of Variable Flow AC Compressor for Commercial Vehicles to Reduce Parasitic Losses
569 and Improving Efficiency of HVAC System. *SAE Technical Paper*, 2018-01-0056.
570 <https://doi.org/10.4271/2018-01-0056>

571 Sjostedt, C.-J., Wikander, J., & Flemmer, H. (2014). *Evaluation of Auxiliary Device Efficiency*
572 *in Heavy Vehicle Application*. ASME 2013 International Design Engineering Technical
573 Conferences and Computers and Information in Engineering Conference.
574 <https://doi.org/10.1115/DETC2013-13395>

575 Troncon, D., Alberti, L., & Mattetti, M. (2019). A Feasibility Study for Agriculture Tractors
576 Electrification: Duty Cycles Simulation and Consumption Comparison. *2019 IEEE*
577 *Transportation Electrification Conference and Expo (ITEC)*, 1–6.
578 <https://doi.org/10.1109/ITEC.2019.8790502>

579 Zhang, Q., Stockar, S., & Canova, M. (2016). Energy-Optimal Control of an Automotive Air
580 Conditioning System for Ancillary Load Reduction. *IEEE Transactions on Control*
581 *Systems Technology*, 24(1), 67–80. <https://doi.org/10.1109/TCST.2015.2418322>

Zhong, L. (2018). Energy Consumption Test and Analysis Methodology for Heavy-Duty Vehicle Engine Accessories. *SAE International Journal of Engines*, 11(5), 539–546. <https://doi.org/10.4271/03-11-05-0036>

Captions

Fig. 1: HVAC compressor, situated on the right side of the tractor, behind the fan drive

Fig. 2: current sensor installed at the alternator output. Alternator current sensor is in the yellow circle.

Fig. 3: the pressure sensor used for monitoring the pressure at the outlet in the yellow circle.

Fig. 4: accessories' characteristic curves of the accessories in the tractor used for the test. alternator (on top left), fan drive (on top right), heating, ventilation and air-conditioning compressor (HVAC) compressor (on bottom left) and of brake air compressor (on bottom right).

Fig. 5: example of signal classifications in function of the tractor operating conditions. A portion of engine power (P_{eng}) (on the left), and a portion of tractor trajectory (on the right) are reported.

Fig. 6: schematisation of the ON/OFF duty cycle used for the characterisation of the HVAC and brake air compressors. t_{pc} and t_{wc} are the pulse period and the pulse width of each cycle, respectively.

Fig. 7: joint probability distribution between battery potential (V_{bat}) and alternator output current (I_{alt}) (on left), and joint probability distribution between the engine speed (n_{eng}) and the alternator power demand (P_{alt}) (on right). The bins where the probability is lower than 0.05% are not displayed.

Fig. 8: joint probability distribution between engine speed (n_{eng}) and fan speed (n_{fan}) (on left), and engine coolant temperature (T_{fan}) and n_{fan} (on right). The bins where the probability is lower than 0.05% are not displayed.

Fig.9: joint probability distribution between engine speed (P_{eng}) and fan drive power demand (P_{fan}). The bins where the probability is lower than 0.05% are not displayed.

Fig. 10: portion of the heating, ventilation and air-conditioning compressor (HVAC) signals used for the calculation of HVAC power demand (P_{HVAC}): HVAC switch status (S_{HVAC}) (first from the top), HVAC compressor engagement (γ_{HVAC}) (second from the top), temperature gradient between actual and setpoint cabin temperatures (ΔT) (third from the top), and P_{HVAC} (forth from the top).

Fig. 11: a portion of the brake air compressor signals: trailer brake compressor pressure (p_{tb}), trailer brake tank pressure (p_{tk}), and trailer brake power demand (P_{BAC}). In particular, two engagements of the compressors can be seen.

Fig. 12: relative power demands (P_{aux}) (on left) and yearly fuel consumption (FC_{aux}) (on right) of alternator (alt), fan drive, heating, ventilation and air-conditioning (HVAC) compressor, and brake air compressor (BAC) according to the operating conditions.