

involved in the project to take the final design solution. Considering the high costs of excavation and underground wall construction, insulation can represent a valid alternative if applied to all rooms. Underground solutions on the contrary can be preferred when excavation is anyhow necessary (for example, if deep foundations are necessary), or in case of specific municipal or landscape protection constraints (*i.e.*, aboveground volume thresholds, landscape integration requirements, *etc.*).

References

- Agenzia Regionale Protezione Ambiente. 2017. ARPAE Idro Meteo Clima. Available from: <https://www.arpae.it/sim/?previsioni/regionali>
- Ayuga F. 1999. Wine processing. In: CIGR Handbook of Agricultural Engineering. St. Joseph, MI, USA, pp. 419-446.
- Barbaresi A., Dallacasa F., Torreggiani D., Tassinari P. 2017. Retrofit interventions in non-conditioned rooms: calibration of an assessment method on a farm winery. *J. Build. Perform. Simulat.* 10:91-104.
- Barbaresi A., De Maria F., Torreggiani D., Benni D., Tassinari P. 2015. Performance assessment of thermal simulation approaches of wine storage buildings based on experimental calibration. *Energy Build.* 103:307-16.
- Barbaresi A., Torreggiani D., Benni D., Tassinari P. 2014. Underground cellar thermal simulation: definition of a method for modelling performance assessment based on experimental calibration. *Energy Build.* 76:363-72.
- Boulton R. 1980. The prediction of fermentation behavior by a kinetic model. *Am. J. Enol. Viticult.* 31:1.
- Boulton R.B., Singleton, V.L., Bisson, L.F., Kunkee, R.E. 1998. Principles and practices of winemaking. Springer, New York, NY, USA.
- Casamonti M., Pavan V. 2004. Cantine architetture 1990-2005. Motta Editore, Milano, Italy.
- Coleman M.C., Fish R., Block D.E. 2007. Temperature dependent kinetic model for nitrogen-limited wine fermentations. *Appl. Environ. Microbiol.* 73:5875-84.
- De Rosi A., Barbaresi A., Torreggiani D., Benni D., Tassinari P. 2014. Numerical simulations of the air flows in a wine-aging room: a lattice Boltzmann-immersed boundary study. *Comput. Electron. Agricult.* 109:261-70.
- Failla A., Tomaselli G., Strano L. 2008. The definition of planning criteria for safe workplaces in wineries. In: Innovation Technology to Empower Safety, Health and Welfare in Agriculture and Agro-food Systems, Ragusa, Italy.
- Fichera C.R., Tomaselli G., Di Fazio S. 1995. La metaprogettazione edilizia per l'industria agraria. Note di metodo. *Riv. Ing. Agr.* 18:45-58.
- Italian Regulation. 2006. Decreto Legislativo 29 dicembre 2006, n. 311 - Disposizioni correttive ed integrative al decreto legislativo 19 agosto 2005, n. 192, recante attuazione della direttiva 2002/91/CE, relativa al rendimento energetico nell'edilizia. In: G.U. Ser. Gen. n. 26, 01/02/2007 - Suppl. Ord. n. 26.
- Jacquet P., Capdeville C. 2007. Installazioni vinicole. Eno-One, Reggio Emilia, Italy.
- Marescalchi C. 1965. Manuale dell'enologo (Winemaking Manual). Fratelli Marescalchi, Casale Monferrato, Italy.
- Martin S., Canas I. 2006. A comparison between underground wine cellars and aboveground storage for the aging of Spanish wines. *Trans. ASABE* 49:1471-8.
- Mazarrón F., Cañas Guerrero I. 2008. Exponential sinusoidal model for predicting temperature inside underground wine cellars from a Spanish region. *Energy Build.* 40:1931-40.
- Mazarrón F., Cid-Falceto J., Cañas Guerrero I. 2012. An assessment of using ground thermal inertia as passive thermal technique in the wine industry around the world. *Appl. Therm. Eng.* 33/34:54-61.
- Notarnicola B., Tassielli G., Nicoletti G.M. 2003. LCA of wine production. In: B. Mattson, U. Sonesson (Eds.), Environmentally-friendly food processing. Woodhead-Publishing and CRC Press, Cambridge-England, Boca Raton, USA, XVII:306-326.
- Ough C.S. 1966. Fermentation rates of grape juice. II effect of initial °Brix, pH, and fermentation temperature. *Am. J. Enol. Viticult.* 17:1.
- Porras-Amores C., Mazarrón F., Cañas Guerrero I. 2014. Study of the vertical distribution of air temperature in warehouses. *Energies* 7:1193-206.
- Reynolds A., Clifford G., Girard B., Kopp T.G. 2001. Influence of fermentation temperature on composition and sensory properties of Semillon and Shiraz Wines. *Am. J. Enol. Viticult.* 52:235-40.
- Rugani P., Vazquez-Roew I., Benedetto G., Benetto E. 2013. A comprehensive review of carbon footprint analysis as an extended environmental indicator in the wine sector. *J. Cleaner Prod.* 54:61-77.
- Tassinari P., Galassi S., Benni S., Torreggiani D. 2009. Il sistema costruito delle aziende vitivinicole: una metodologia di analisi del comparto per la definizione dei requisiti metaprogettuali. In: IX Convegno Nazionale dell'Associazione Italiana di Ingegneria Agraria, pp. 12-16.
- Tassinari P., Torreggiani D., Benni S., Dall'Ara E. 2013. Landscape quality in farmyard design: an approach for Italian Wine farms. *Landscape Res.* 38:729-49.
- Tinti F., Barbaresi A., Benni S., Torreggiani D., Bruno R., Tassinari P. 2014. Experimental analysis of shallow underground temperature for the assessment of energy efficiency potential of underground wine cellars. *Energy Build.* 80:451-60.
- Tinti F., Barbaresi A., Benni S., Torreggiani D., Bruno R., Tassinari P. 2015. Experimental analysis of thermal interaction between wine cellar and underground. *Energy Build.* 104:275-86.
- Torreggiani D., Benni S., Garcia A.I., Ayuga F., Tassinari P. 2014. Farm winery layout design: size analysis of base spatial units in an Italian study area. *Trans. ASABE* 57:625-33.
- Ventura F., Facini O., Gorgiadis T., Nardino M., Rossi F. 2007. Indagine sui flussi di materia ed energia da vigneto e daterreno nudo nell'interfilare in un sistema viticolo dell'Italia Centrale. *Quad. Viticolt. Enol.* 27-41.
- Zamora F. 2003. Elaboracion y crianza del vino tinto: aspectos científicos y prácticos. Mundi-Pren., Madrid, Spain.