

Alma Mater Studiorum Università di Bologna  
Archivio istituzionale della ricerca

A comparison of equivalent noise methods in investigating local and global form and motion integration

This is the final peer-reviewed author's accepted manuscript (postprint) of the following publication:

*Published Version:*

Pavan, A., Contillo, A., Yilmaz, S.K., Kafaligonul, H., Donato, R., O'Hare, L. (2023). A comparison of equivalent noise methods in investigating local and global form and motion integration. ATTENTION, PERCEPTION & PSYCHOPHYSICS, 85, 152-165 [10.3758/s13414-022-02595-z].

*Availability:*

This version is available at: <https://hdl.handle.net/11585/914571> since: 2024-12-06

*Published:*

DOI: <http://doi.org/10.3758/s13414-022-02595-z>

*Terms of use:*

Some rights reserved. The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website.

This item was downloaded from IRIS Università di Bologna (<https://cris.unibo.it/>).  
When citing, please refer to the published version.

(Article begins on next page)

1  
2  
3  
4 **A Comparison of Equivalent Noise Methods in Investigating Local and Global**  
5 **Form and Motion Integration**  
6  
7  
8

9 Andrea Pavan<sup>1,\*</sup>, Adriano Contillo<sup>2</sup>, Seyma Koc Yilmaz<sup>3</sup>, Hulusi Kafaligonul<sup>3,4</sup>, Rita Donato<sup>5,6,7</sup>, &  
10 Louise O'Hare<sup>8</sup>  
11

12  
13  
14 <sup>1</sup> University of Bologna, Department of Psychology, Viale Berti Pichat, 5, 40127, Bologna, Italy

15 <sup>2</sup> Elettra-Sincrotrone Trieste S.C.p.A, Trieste, Italy

16  
17 <sup>3</sup> National Magnetic Resonance Research Center, Bilkent University, Ankara, Turkey

18  
19  
20 <sup>4</sup> Interdisciplinary Neuroscience Program, Aysel Sabuncu Brain Research Center, Bilkent University,  
21 Ankara, Turkey

22  
23 <sup>5</sup> Department of General Psychology, University of Padova, Padova, Italy

24  
25 <sup>6</sup> Proaction Laboratory, Faculty of Psychology and Educational Sciences, University of Coimbra,  
26 Coimbra, Portugal

27  
28 <sup>7</sup> CINEICC, University of Coimbra, Faculty of Psychology and Educational Sciences, Rua Colégio  
29 Novo, 3000-115 Coimbra, Portugal

30  
31 <sup>8</sup> Department of Psychology, Nottingham Trent University, Nottingham, United Kingdom  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41

42 **\*Corresponding Author**

43 Andrea Pavan

44 University of Bologna

45 Department of Psychology

46 Viale Berti Pichat, 5, 40127, Bologna, Italy

47 Email: [andrea.pavan2@unibo.it](mailto:andrea.pavan2@unibo.it)  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

**Abstract**

Static and dynamic cues within certain spatiotemporal proximity are used to evoke respective global percepts of form and motion. The limiting factors in this process are first, internal noise, which indexes local orientation/direction detection, and secondly, sampling efficiency, which relates to the processing and the representation of global orientation/direction. These parameters are quantified using the equivalent noise (EN) paradigm. EN has been implemented with just two levels: high and low noise. However, when using this simplified version, one must assume the shape of the overall noise dependence, as the intermediate points are missing. Here, we investigated whether two distinct EN methods, the eight-point, and the simplified two-point version, reveal comparable parameter estimates. This was performed for three different types of stimuli: random dot kinematograms, and static and dynamic translational Glass patterns, to investigate how constant internal noise estimates are, and how sampling efficiency might vary over tasks. The results indicated substantial compatibility between estimates over a wide range of external noise levels sampled with eight data points, and a simplified version producing two highly informative data points. Our findings support the use of a simplified procedure to estimate essential form-motion integration parameters, paving the way for rapid and critical applications to populations that cannot tolerate protracted measurements.

**Keywords:** Internal noise, sampling efficiency, form-motion integration, equivalent noise methods

## Introduction

Looking at the natural world, we see objects of various colors and shapes that are either stationary or moving in different directions. How the human visual system merges local inputs into a global coherent perceptual scene is an important question in vision research. Numerous studies have investigated how local form features or local motion signals are combined to generate a coherent global motion or form percept (Allard & Arleo, 2021; Anstis & Kim, 2011; Cropper, 2001; Hoffman, 1980; Loffler et al., 2003; McKendrick et al., 2005). According to psychophysical studies, internal noise and sampling efficiency are two primary elements that influence the perception of global form and motion (Bogfjellmo et al., 2013; Falkenberg et al., 2002, 2014; Joshi et al., 2021; Simpson et al., 2003; Tibber et al., 2014). In the case of the visual system, internal noise is the limit of the visual system to detect cues in the absence of noise. Sampling efficiency refers to the ability to combine individual elements to create a global percept of the visual stimulus of interest (e.g., Dakin et al., 2005).

A method to quantify the internal noise and sampling efficiency is the equivalent noise (EN) analysis (e.g., Dakin et al., 2005; Tibber et al., 2014; Baldwin et al., 2016). The EN analysis has its roots in engineering – to test the level of noise inherent in a system, one introduces a very small, imperceptible signal, and begins to increase it. When this signal has increased to a level that it is just perceptible, this is the equivalent to the internal noise of the system itself. The concept of equivalent noise analysis dates to the work of Barlow in the 1950s based on assessing detection performance. Barlow (1957) argued that the ability of the visual system to detect near-threshold stimuli was influenced by factors such as the number of photons absorbed by the eye as well as “dark light” the spontaneous neural activity (Barlow, 1957). In later work, there has been a tradition of using the “ideal observer” as a comparison for estimating the efficiency of the visual system (Geisler, 1989; Geisler, 2003). The “ideal observer” is a model of the physiological limits of the visual system, including such factors as photon noise, chromatic aberrations, effects of the lens, and eye movements (Geisler, 2003), as well as spatial summation from retinal ganglion cells (Banks et al., 1991). When these “pre-neural” factors are accounted for (as the “ideal observer”), the difference in performance between the real human performance and the ideal observer must be the result of later, neural processing. In addition, pixel noise can be used in conjunction with the ideal observer analysis (Geisler, 2003).

The ideal observer (or ideal discriminator) analysis has been used in the case of various visual processes including detection (Barlow, 1957), blur (Watt & Morgan, 1984) and motion perception (e.g., Watamaniuk et al., 1989, 1993, 1999, 2011). The efficiency of the human visual system is much

1  
2  
3  
4 lower than that of the ideal observer, however, in some cases (e.g., chromatic contrast sensitivity), the  
5 efficiency is relatively high compared to the ideal observer (Geisler, 1989). Efficiency compared to the  
6 ideal observer is not the same as performance, as if the task is impossible, the ideal observer also  
7 performs poorly, and so the human observer may be quite efficient in comparison, despite task  
8 performance being poor.  
9

10  
11 In the case of form and motion perception, the estimate of internal noise depends on the ability  
12 of the observer to detect the local variance in orientation or motion direction of the single elements  
13 forming a visual pattern (Dakin et al., 2005; Joshi et al., 2021). To estimate sampling efficiency, the  
14 ability of the system to pool visual information is tested. In other words, for the direction integration of  
15 drifting dots, internal noise would affect the precision of estimating each dot's direction, whereas  
16 sampling efficiency refers to the number of such estimates that can be averaged over (Dakin et al.,  
17 2005). Furthermore, the direction or the orientation of the individual cues that form a visual pattern is  
18 derived by a Gaussian distribution with a prescribed mean and standard deviation, in which all the local  
19 cues are assigned with independent local directions or orientations along the mean of the underlying  
20 distribution (Watamaniuk & Sekuler, 1992). The sampling efficiency is estimated by manipulating the  
21 variance of a specific motion direction or the variance of stimulus orientation (Dakin et al., 2005;  
22 Tibber et al., 2014), and relies on global processing. In this case, sampling efficiency is not a result of  
23 the observer's ability to rule out noise; rather, it is the consequence of the best strategy for integrating  
24 the orientations/directions of a visual stimulus. It is important to note that the "best" strategy in human  
25 visual performance is often not efficient when compared to a model of the physiological limitations  
26 (Geisler, 1989, 2003; Watamaniuk 1993). A linear amplifier model of the EN can be utilized to derive  
27 the values associated with internal noise and sampling efficiency from the performance of participants  
28 (Pelli & Farell, 1999).  
29

30  
31 Internal noise estimates are thought to be relatively stable within an observer (Baker, 2013), but  
32 sampling efficiency varies between different tasks that rely on global form or global motion (Joshi et  
33 al., 2021). There are two types of visual stimuli useful to study local versus global processing of  
34 motion/orientation and form-motion interactions: Glass patterns (GPs) (Glass, 1969) and Random Dot  
35 Kinematograms (RDKs) (Ghin et al., 2018; Joshi et al., 2016, 2020, 2021; O'Hare et al., 2021; Pavan et  
36 al., 2019). Static GPs are made of single pairs of dots called dipoles and are used to estimate global  
37 form perception. The local orientations of dipoles give rise to various global configurations such as  
38 translational, radial, spiral, circular, etc. GPs can be either static or dynamic. Dynamic GPs, instead, are  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57

1  
2  
3  
4 made of a succession of unique static GPs where each frame is independent and dipoles do not follow  
5 an exact trajectory across the frames, but they only maintain constant global orientation (Donato et al.,  
6 2021; Krekelberg et al., 2003, 2005; Nankoo et al., 2012; Pavan et al., 2017a, 2017b, 2021). Although  
7 dynamic GPs do not have a dipole-to-dipole correspondence across frames, they do give the impression  
8 of motion along the dipoles' orientation axis (Joshi et al., 2020; Ross et al., 2000). Some studies call  
9 the percept of motion generated by dynamic GPs *implied motion* (Krekelberg et al., 2003, 2005; Joshi  
10 et al., 2020). However, in psychophysical studies, the term *implied motion* is usually referred to motion  
11 implied in still pictures or photographs (Friedman & Stevenson, 1975; Lorteije et al., 2006; Pavan et  
12 al., 2011; Yamamoto & Miura, 2012). To prevent misinterpretations, we will refer to the motion  
13 elicited by dynamic GPs as *non-directional motion* (Donato et al., 2020, 2021; Pavan et al., 2021). To  
14 estimate directional motion perception, as opposed to non-directional motion evoked by form cues,  
15 RDKs consist of an array of moving dots and unlike GPs, are not arranged into dot pairs (dipoles)  
16 (Donato et al., 2020; Rajananda et al., 2018).

17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

There are important distinctions between form and motion perception. Local detection in static GPs is thought to take place in early visual areas, such as V1 (Dakin, 1997), and the global pooling thought to take place in V4 (Wilson & Wilkinson, 1998). In global motion, local detection is thought to take place in V1, with integration of motion in later stages, such as V2, V3, and hMT+ for translational and complex motion (e.g., radial and expansion/contraction motion) (Beardsley & Vaina, 1998, 2001; Furlan & Smith, 2016; Morrone et al., 1995). However, there is also interdependence of motion and form perception as in the case of dynamic GPs. Indeed, non-directional motion from dynamic GPs seems to use both form and motion processes. Some studies have reported that local processing in dynamic GPs (i.e., dipole orientation) takes place at the early level of the visual system (i.e., V1/V2) (Donato et al., 2020; Pavan et al., 2017; Ross et al., 2000). There is also evidence of dynamic GPs activating higher visual areas, such as hMT+ (Pavan et al., 2017). This is important as it shows that the visual system seems to process directional motion evoked by RDKs similarly to dynamic GPs (Krekelberg et al., 2003, 2005), which is probably responsible for the illusory directional motion that observers report when they look at a dynamic GP (Joshi et al., 2021; Krekelberg et al., 2005).

Form and motion processing can be explored through the EN paradigm (Joshi et al., 2021). There is a simplified version of the EN paradigm, with only two sampling points, one at zero stimulus variance, and one at high stimulus variance. This simplified version has been used with children (Manning et al., 2014; Falkenberg et al., 2014), children with reading difficulties (Manning et al.,

2022), children with autism (Manning et al., 2015, 2017), and in clinical populations such as those with amblyopia (Joshi et al., 2016), migraine (Tibber et al., 2014; O’Hare et al., 2021), and schizophrenia (Tibber et al., 2015). The simplified version is a benefit with these populations as it dramatically reduces the number of trials for the participant. However, these simplified EN paradigms using only high and low noise levels neglect intermediate points and failing to examine the entire form of noise dependence. In the current study, we investigated whether the simplified and the multisampling EN paradigms produce comparable outcomes for static translational GPs, dynamic translational GPs, and RDKs. In the multiple-point EN paradigm, we used eight staircases to monitor the minimal discriminable angle at a certain external noise level by manipulating the mean orientation/direction. In the simplified method we used two staircases as in previous work (e.g., Tibber et al., 2014): one that adaptively changes the mean orientation/direction to track minimum discriminable offset in the absence of external noise, and another that manipulates the standard deviation to track maximum tolerable noise level at a fixed mean orientation/direction. If the widely used simplified procedure is valid, then there will be comparable estimates between the two methods for form, non-directional, and directional motion EN tasks.

## Methods

### *Participants*

Two of the authors (RD and SKY) and eleven naïve observers (7 females, mean age =  $23.5 \pm 1.9$  years) took part in the experiment. All participants reported normal or corrected-to-normal visual acuity. The sample size was estimated a priori using G\*Power (v3.1; Faul, Erdfelder, Buchner, & Lang, 2009) and based on a repeated measures ANOVA (within-subjects factors) to possibly detect a difference between procedures, stimulus type, and the interaction between main effects. Correlation was factored into the effect size using the SPSS option for effect size specification. Based on Joshi et al. (2021), assuming a large effect size  $f$  of .4 (Cohen, 2013) to achieve a Power level of 95% (at the alpha level of .05) with one group of participants, and assuming sphericity, the Power analysis suggested a sample of ten participants. This is for 27 experimental levels in total, consisting of eight noise levels for the 8-point procedure plus a data point (high-noise level) for the 2-point procedure (and so nine in total) x three stimulus patterns (RDK, static GP, and dynamic GP). We slightly extended the suggested sample size by including three additional participants, achieving a Power of 99%. The final sample of 13 participants was also compatible with the previous reports of EN analysis (Ghin et al.,

1  
2  
3  
4 2018). The study was conducted in accordance with the World Declaration of Helsinki (2013) and  
5 approved by the Human Research Ethics Committee of Bilkent University (Ethics protocol number:  
6 2021.10.04.03). Prior to their participation, all participants signed written informed consent. The naïve  
7 participants received monetary compensation (50 TL) for completing the experiment.  
8  
9

### 10 11 12 *Apparatus*


13 Stimuli were generated using MATLAB with the Psychophysics Toolbox (Brainard, 1997;  
14 Pelli, 1997; Kleiner et al., 2007) and displayed on a 24.5-inch Dell Alienware AW2521HFL IPS  
15 monitor with a refresh rate of 60 Hz. The screen resolution was 1280 x 1024 pixels. Each pixel  
16 subtended 2.8 arcmin. The screen luminance was measured using a SpectroCAL photometer  
17 (Cambridge Research Systems, Rochester, Kent, UK). The stimuli were presented on a gray  
18 background (42.78 cd/m<sup>2</sup>). Observers sat in a dark room at a viewing distance of 57 cm from the  
19 screen. Viewing was binocular. Head movements were constrained by a chinrest.  
20  
21  
22  
23  
24  
25  
26  
27

### 28 29 *Stimuli*

30 Stimuli were RDKs, static and dynamic translational GPs (see Figure 1A). All three stimulus  
31 patterns were composed of 500 white dots (diameter: 0.083 deg, luminance: 247.80 cd/m<sup>2</sup>, Weber  
32 contrast: 4.79). The ensemble of dots was presented at the center of the screen within a circular  
33 aperture with a diameter of 10.0 deg (density: 6.37 dots/deg<sup>2</sup>). A black fixation point (diameter: 0.3  
34 deg, luminance: 0.31 cd/m<sup>2</sup>) and a black vertical line (length: 2.3 deg, width: 0.047 deg) were presented  
35 at the center of the screen. The vertical line served as a reference, and it was used to judge whether the  
36 overall pattern drifted or was tilted clockwise or counter-clockwise from vertical. Stimulus duration  
37 was 500 ms. In the RDKs, the dots drifted at a speed of 10.0 deg/s. Each dot followed a trajectory for a  
38 limited lifetime of 83 ms (i.e., five screen refreshes), after which it was randomly relocated within the  
39 circular window to prevent covert attentional tracking of the motion direction. The static GPs were  
40 composed of 250 pairs of dots (i.e., dipoles). The dipoles were formed by a linear geometrical  
41 transformation. The dipole distance was 0.2 deg. The dynamic GPs were generated by rapid sequential  
42 presentation of a set of independent static GPs (temporal frequency: 10 Hz). In the dynamic GPs, while  
43 the spatial arrangement of dipoles was altered in each six-frame cycle, the overall orientation was kept  
44 constant evoking the perception of non-directional apparent motion along this orientation (Donato et  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60



al., 2021; Nankoo et al., 2012; Pavan et al., 2021; Ross et al., 2000). Directional or orientational noise was added to these stimuli as described below.



**Figure 1.** Stimulus patterns and added noise in the equivalent noise paradigm. (A) Three representative frames for each stimulus type. For illustrative purposes, one dot was enlarged in the random dot kinematogram to indicate the upper leftward drift. In the static Glass pattern, one dipole was enlarged to indicate the counter-clockwise orientation and the position of the dipoles was constant throughout a given trial. In the dynamic Glass pattern, one dipole in each frame was enlarged to indicate the counter-clockwise orientation, and the position of the dipoles was changed every six frames throughout a given trial. Please note, in the actual experiment no dot was enlarged. For demonstrative purposes, for all the stimuli the direction/orientation was set to 30 deg counter-clockwise with respect to the vertical

1  
2  
3  
4 reference, and the noise level was set to zero deg. **(B)** Angle histograms illustrate the distribution of the  
5 eight-point procedure's motion directions/orientations for each noise level. The mean of the distribution  
6 (i.e., the global direction/orientation) was fixed at 120 deg (i.e., 30 deg counter-clockwise from the  
7 vertical) for easier comparison between the standard deviation values.  
8  
9

### 10 11 12 *Equivalent Noise Paradigm*

13  
14 Visual sensitivity to global directional/real motion, form, and non-directional/apparent motion  
15 was measured using the EN approach. Global motion and form perception has been typically studied  
16 utilizing coherence tasks, in which random elements are introduced to the stimulus and the procedure is  
17 aimed at specifying the amount of these randomly moving/oriented elements that can replace the  
18 coherent ones without disrupting reliable discrimination (Britten et al., 1992; Grossman, & Blake,  
19 1999; Snowden, & Kavanagh, 2006). There is clearly a distinction between signal and noise elements  
20 in the coherence tasks. On the contrary to this approach, in the EN paradigm all the individual elements  
21 are defined as signal, as they contribute to the global motion/form. This is accomplished by assigning  
22 the direction/orientation of dots/dipoles based on a Gaussian distribution around a given mean value. In  
23 this case, the variability in direction/orientation is introduced by varying the standard deviation of the  
24 Gaussian distribution (Watamaniuk & Sekuler, 1989; Watamaniuk, 1993).  
25  
26  
27  
28  
29  
30  
31


32  
33 In the current study, we implemented two variants of the EN paradigm to estimate  
34 discrimination thresholds and accordingly, compute internal noise and sampling efficiency parameters  
35 for the three types of stimulus patterns. One of these methods sampled multiple points over a range of  
36 external noise levels (Joshi et al., 2021) and the other one simplified the procedure to a high- and a  
37 zero-noise level (Ghin et al., 2018; O'Hare et al., 2021; Pavan et al., 2019; Tibber et al., 2014).  
38  
39  
40

41  
42 In the multiple sampling procedure (i.e., eight-point method), all the individual elements within  
43 each pattern were assigned with independent local directions/orientations along the mean of a circular  
44 Gaussian distribution. Mean motion directions or orientations were perturbed by varying the standard  
45 deviation of the underlying distribution. Specifically, the eight-point method employed staircases  
46 manipulating the mean direction/orientation to track the minimum discriminable angle at a given  
47 external noise level ( $\sigma = 0, 2, 4, 8, 16, 24, 32, \text{ or } 40$  deg; see Figure 1B). The simplified two-point  
48 method, on the other hand, employed two independent staircases, one adaptively changing the mean  
49 orientation/direction to track the minimum discriminable angle in the absence of external noise ( $\sigma = 0$   
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

deg), and the other manipulating the standard deviation to track the maximum tolerable noise level at a fixed mean orientation/direction.

### Procedure

Figure 2 shows the trial sequence used in the experiment. Each trial started with a fixation point and a vertical line crossing the fixation marker presented for 1.0 s. The fixation screen was followed by the presentation of a RDK or a GP (either static or dynamic) with a duration of 0.5 s. The response screen was identical to the fixation screen and endured until a response was made plus for an additional inter-trial-interval of 1.0 s. The observers performed a two-alternative forced-choice (2AFC) global motion direction or orientation discrimination task. They indicated whether the moving dots/oriented dipoles drifted/were tilted clockwise or counter-clockwise from vertical. They were instructed to press the left arrow key if the overall pattern was perceived to drift/tilted counter-clockwise with respect to the vertical reference or the right arrow key if it was perceived to drift/tilted clockwise from vertical.



**Figure 2.** Schematic representation of a trial sequence. For demonstrative purposes, the stimulus is a static Glass pattern with zero noise ( $\sigma = 0$  deg) and tilted counter-clockwise from vertical by 30 deg ( $\mu = 120$  deg). RDK: Random Dot Kinematogram, SGP: Static Glass Pattern, DGP: Dynamic Glass Pattern, ITI: Inter-trial Interval.

The observers completed four experimental sessions that were ran in four non-consecutive days. Three sessions were allocated to the eight-point procedure, each session comprising one type of the stimulus patterns (i.e., RDKs, static GPs, or dynamic GPs). The remaining session was allocated to the

1  
2  
3  
4 two-point procedure, including all types of the stimulus patterns. The order of sessions was randomized  
5 to avoid sequence effects.

6  
7 The eight-point procedure was characterized by a staircase procedure running with a 1-up/3-  
8 down rule tracking the 79.4% discrimination threshold (Levitt, 1971; Wetherill & Levitt, 1965). In each  
9 block including a specific noise level, two interleaved and randomized staircases were administered,  
10 one starting from 30 deg clockwise from vertical and another starting from 30 deg counter-clockwise  
11 from vertical. Within each block, the external noise was kept constant at one of the eight levels and the  
12 mean direction/orientation was adaptively changed to track the minimum angle offset from vertical that  
13 can be reliably discriminated. The step size was initially 15 deg and it was decreased to half, quarter,  
14 and ultimately one-eighth of an octave for each subsequent reversal (i.e., 15.0, 7.5, 3.75, 1.875 deg).  
15  
16 After the fourth reversal, the step size was fixed at 1.875 deg. The relatively large step size was chosen  
17 as this was a similar magnitude to the work by Joshi et al. (2021). Additionally, although previous work  
18 has shown thresholds of less than 2 degrees including experienced psychophysical observers  
19 (Watamaniuk & Sekuler, 1992), the observers in the current study were largely inexperienced in terms  
20 of psychophysics and so the larger step size was used to better match their ability. Individual thresholds  
21 for each stimulus pattern can be seen in the Supplementary material (Table S1). Each staircase  
22 terminated after either 100 trials or 20 reversals. The threshold was calculated as follows: in the case of  
23 the 8-point procedure, in which there are two interleaved staircases for each stimulus pattern, we  
24 gathered the reversals of both staircases, ordered them with respect to the corresponding trials, and then  
25 computed the average of the last six of them. Such a choice was motivated by the fact that some  
26 staircases (which are shorter than those of the 2-point procedure) exhibited only a limited number of  
27 reversals, happening early in the staircase, and reducing the step almost immediately. In these cases,  
28 the above-described computation spontaneously neglects these reversals, avoiding possible systematics  
29 in the threshold estimate. It should be noted that the staircases of one participant (S10) proved to be  
30 unusable, with very high thresholds and uncertainties of various orders of magnitude greater than the  
31 other participants in most of the conditions. Since this would have excluded the contribution of the  
32 participant from the calculation of the statistics (infinite uncertainty corresponds to zero weight), the  
33 participant was excluded from the analyses (see Figure S1 in the Supplementary material). For the 2-  
34 point procedure the threshold was calculated by averaging the last six reversal of the staircase. Each  
35 session in this procedure was preceded by a short practice consisting of 16 trials ( $\mu = 30$  deg,  $\sigma = 0$  deg)  
36 to familiarize the participants with the relevant stimulus pattern and discrimination task. Each block  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

1  
2  
3  
4 within a session started with a 10-trial practice having the same noise level as in the relevant block. In  
5 the practice trials, 0.5-second-long feedback was provided after the response, by turning the fixation  
6 point to green for correct responses and red for incorrect responses.  
7

8  
9 In the two-point procedure, for the first point (i.e., zero noise level) we used the output of the  
10 first point from the eight-point procedure. For the second point, which included noise, a staircase with a  
11 3-up/1-down rule was used to vary the standard deviation of the Gaussian distribution, while the mean  
12 direction/orientation remained at 45 deg clockwise or counter-clockwise across trials. The initial noise  
13 level was zero deg and the noise level was increased/decreased with a fixed step size of 5 deg. The  
14 staircase terminated after either 200 trials, or 20 reversals and the threshold was calculated by  
15 averaging all the reversals. At the beginning of each block, there were 16 practice trials ( $\mu = 45$  deg)  
16 with a noise level randomly chosen between 8 deg and 64 deg, in steps of 8 deg.  
17  
18

19 For both eight-point and two-point procedures, 10 catch trials without external noise were  
20 randomly inserted in each block to make sure that the participants performed the task according to the  
21 instructions. The average accuracy in catch trials was 96% for both procedures. In addition, the mean  
22 accuracy scores were above 89% for each noise level within each stimulus type. The observers received  
23 no feedback on these trials. The order of blocks in each session was randomized and the  
24 direction/orientation (left or right) was randomly selected for each trial.  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34

### 35 *Data Analysis*

36 For each observer, discrimination thresholds estimated with the 2-point procedure were used to  
37 compute the *internal noise* ( $\sigma_{int}$ ) and the *sampling efficiency* ( $\eta$ ) estimates according to Ghin et al.  
38 (2018), where the EN parameterization:  
39  
40  
41

$$42 \sigma_{obs} = \sqrt{\frac{\sigma_{int}^2 + \sigma_{ext}^2}{\eta}} \quad \text{Eq. (1)}$$

43  
44 is constrained by two threshold values: a zero-noise (at fixed  $\sigma_{ext} = 0$ ) data point, which represents the  
45 minimum directional offset from vertical that can be discriminated with no external noise, and a high-  
46 noise (at fixed  $\sigma_{obs}$ ) data point, which represents the maximum level of noise (i.e., the directional  
47 standard deviation of the normal distribution of directions) that can be tolerated for a large directional  
48 offset. The rationale behind such choice is that two points with orthogonal uncertainties (fixed external  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

noise and varying observed noise for the former, the opposite for the latter) are highly effective at constraining the two EN parameters, each dominant in the regime spanned by one of the data points. In fact, at zero noise, Eq. (1) becomes:

$$\sigma_{obs,0} = \frac{\sigma_{int}}{\sqrt{\eta}} \quad \text{Eq. (2)}$$

while at high noise, where  $\sigma_{ext,H} \gg \sigma_{int}$ , it becomes:

$$\sigma_{obs,H} \simeq \frac{\sigma_{ext,H}}{\sqrt{\eta}} \quad \text{Eq. (3)}$$

and the system composed by Eqs (2) and (3) can be solved in terms of the EN parameters giving:

$$\eta = \frac{\sigma_{ext,H}^2}{\sigma_{obs,H}^2} \quad \text{and} \quad \sigma_{int} = \sigma_{obs,0} \sqrt{\eta} \quad \text{Eq. (4)}$$

The uncertainties associated to the retrieved parameters can be propagated from the measured uncertainties on the data points,  $\delta\sigma_{obs,0}$  for the zero-noise point and  $\delta\sigma_{ext,H}$  for the high-noise one. Such propagations read:


$$\delta\eta = \frac{2\sigma_{ext,H}}{\sigma_{obs,H}^2} \delta\sigma_{ext,H} \quad \text{and} \quad \delta\sigma_{int} = \sqrt{\eta(\delta\sigma_{obs,0})^2 + \frac{\sigma_{obs,0}}{4\eta} (\delta\eta^2)} \quad \text{Eq. (5)}$$

The 8-point procedure was tackled instead with a best fit of the data points against the parameterization function. However, given its power-law behavior, a log-log version was used for the best fit:

$$y = \ln\left(\sqrt{\frac{e^{2x} + \sigma_{int}^2}{\eta}}\right) \quad \text{Eq. (6)}$$

which is equivalent to Eq. (1) if  $x = \ln\sigma_{ext}$  and  $y = \ln\sigma_{obs}$ . Such choice, resulted in a general increase in quality of the fits, from which the EN parameters were retrieved. The associated uncertainties were

also obtained from the best fit. Figure 3 shows an exemplary comparison between a 2-point and an 8-point procedure for a single participant.



**Figure 3.** An exemplary representation of a 2-point procedure (red dots) and an 8-point procedure (blue dots), in terms of the logarithmic variables  $x = \ln \sigma_{ext}$  and  $y = \ln \sigma_{obs}$ . The three panels represent a single participant's different stimuli (A: dynamic GPs; B: RDKs; C: static GPs). The single point to the

1  
2  
3  
4 left of the axis break represents the zero-noise condition, which is common to both procedures. The 2-  
5 point procedure data points display their associated measurement uncertainties, from which the  
6  
7 uncertainties on the EN parameters will be propagated. For the 8-point procedure, the log-log best fit  
8  
9 with the associated 95% confidence interval is displayed alongside the data points.  
10

11  
12 We used a different method of analysis compared to that of Joshi et al. (2021). We compared  
13 the effects of procedure (2-point and 8-point method), stimulus type (static and dynamic Glass patterns,  
14 RDKs) and their interactions on the internal noise and sampling efficiency estimates by fitting  
15  
16 Generalized Linear Models (GLM) (Fox, 2003) on individual data, rather than group data. Specifically,  
17 the EN parameters pertaining to each observer were analyzed using a GLM with 'lme4' package (Bates  
18 et al., 2015). The analyses were performed using R (v4.2.1) (R Core Team 2022). Input data to the  
19  
20 model were weighted for the reciprocal of their standard deviation ( $1/\sigma$ ). For internal noise ( $\sigma_{int}$ ) and  
21  
22 sampling efficiency ( $\eta$ ), a Gamma distribution and identity link transformation function were used in  
23  
24 the GLM model. We chose a Gamma distribution for the regression analysis because data were well  
25  
26 approximated by a Gamma distribution and almost all the *internal noise* ( $\sigma_{int}$ ) values fell into the  
27  
28 Gamma quantiles, allowing us to deal with outliers without removing or transforming them (Zuur et al.,  
29  
30 2010). We created five different models that included only the main effect of the stimulus (model 1),  
31  
32 only the main effect of the procedure (model 2), both main effects (model 3), the interaction term only  
33  
34 (model 4), and the main effects plus the interaction term (model 5). The best fitting model was selected  
35  
36 using the estimators of prediction error *AIC* and *AICc* (i.e., the *AIC* with a correction for small sample  
37  
38 sizes). In the case of the *internal noise*, the best fitting model was shown to be the one where there was  
39  
40 only the effect of the procedure, not of stimulus, or any interaction. Therefore, the model output for  
41  
42 *internal noise* has only estimates for the two procedures (see Figure 4A). For the *sampling efficiency* ( $\eta$   
43  
44 ) estimate, the best fitting model was the one including the main effects of stimulus and procedure, and  
45  
46 the interaction; this can be seen in Figure 4B. Outliers were identified using the median absolute  
47  
48 deviation with a cut-off of 3 (Leys et al., 2013). The mean values and 95% confidence intervals  
49  
50 correspond to the output of the Generalized Linear Models. Predictions and partial residuals of the best  
51  
52 fitting GLMs for *internal noise* and *sampling efficiency* are reported in the Supplementary material  
53  
54 (Figure S2).  
55  
56  
57  
58  
59  
60



## Results

Figure 4 shows the results of the *Equivalent Noise* analysis for both procedures. For *internal noise* ( $\sigma_{int}$ ), a Shapiro–Wilk test showed that residuals were not normally distributed ( $W = .642, p < .0001$ ), with a high positive skewness of 4.0 ( $SE = .282$ ). We identified four outliers that were included in the analysis ( $\sigma_{int} > 19^\circ$ ). The best fitting model (with the lowest *AIC* and *AICc*) included only the main effect of the procedure (model 2) (see Table S2 in the Supplementary material for model selection). However, the regression analysis did not reveal a significant effect of the procedure ( $\chi^2 = 1.294, df = 1, p = .2553$ ). The parameters of the best fitting model are reported in Table 1. Predicted *internal noise* values with partial residuals for the two procedures are reported in the Supplementary material (see Figure S2A).

<i>Internal noise</i> ( $\sigma_{int}$ )				
<i>Predictors</i>	<i>Estimates</i>	<i>SE</i>	<i>t</i>	<i>p</i> ( $>  t $ )
(Intercept)	5.53	.82	<b>6.751</b>	<b>&lt;.001</b>
Procedure [8-point]	-1.048	.96	-1.089	.28
Observations			72	
<i>log-Likelihood</i>			-77.590	
<i>AIC</i>			161.18	
<i>AICc</i>			161.53	


**Table 1.** Estimated coefficients of the Generalized Linear Model fitted on *internal noise* data with weights. Standard error, *t* statistics, and *p*-values for model intercept and procedure are reported. Under the assumptions of linear regression, the estimated regression coefficients follow a Student's *t*-distribution. The *p*-values indicate how often a coefficient of that magnitude would be found by chance if the coefficient was zero with that standard error.

For *sampling efficiency* ( $\eta$ ), a Shapiro–Wilk test showed that residuals were not normally distributed ( $W = .706, p < .0001$ ), with a positive skewness of 1.877 ( $SE = .282$ ). We identified eight outliers ( $9.325 \leq \eta \leq 12.695$ ) that were included in the analysis. The best fitting model included main effects (stimulus type and procedure) and the interaction term (model 5) (see Table S2 in the Supplementary material for model selection). The regression analysis revealed only a significant effect

of the stimulus type ( $\chi^2 = 29.324$ ,  $df = 2$ ,  $p < .0001$ ), but not for procedure ( $\chi^2 = .005$ ,  $df = 1$ ,  $p = .94$ ) or stimulus type x procedure interaction ( $\chi^2 = 1.838$ ,  $df = 2$ ,  $p = .398$ ). Holm corrected post hoc comparisons for the stimulus type revealed a significant difference between RDKs and dynamic GPs ( $p_{adj} = .01$ ), between RDKs and static GPs ( $p_{adj} = .005$ ), but not between the two GP types ( $p_{adj} > .05$ ). The parameters of the best fitting regression model are reported in Table 2. Predicted *sampling efficiency* values with partial residuals for the stimulus patterns used are reported in the Supplementary material (see Figure S2B). Taken together these results suggest that the two EN procedures produce similar results. *Internal noise* and *sampling efficiency* values for each participant and experimental condition are reported in the Supplementary material (see Table S3).

<i>Sampling efficiency</i> ( $\eta$ )				
<i>Predictors</i>	<i>Estimates</i>	<i>SE</i>	<i>t</i>	<i>p</i> ( $>  t $ )
(Intercept)	0.93	0.15	<b>6.08</b>	<b>&lt;0.001</b>
Stimulus [RDK]	2.28	0.87	<b>2.62</b>	<b>0.009</b>
Stimulus [SGP]	0.08	0.24	0.33	0.743
Procedure [8-point]	0.31	0.36	0.86	0.389
Stimulus [RDK] * Procedure [8-point]	-0.88	1.27	-0.69	0.488
Stimulus [SGP] * Procedure [8-point]	-0.53	0.44	-1.21	0.226
Observations	72			
<i>log-Likelihood</i>	-166.852			
<i>AIC</i>	347.704			
<i>AICc</i>	349.454			

**Table 2.** Estimated coefficients of the Generalized Linear Model fitted on *sampling efficiency* data with weights. Standard error, *t* statistics, and *p*-values for model intercept, and stimulus predictors are reported. Under the assumptions of linear regression, the estimated regression coefficients follow a Student's *t*-distribution. The *p*-values indicate how often a coefficient of that magnitude would be found by chance if the coefficient was zero with that standard error.



**Figure 4.** Results of the equivalent noise analysis ( $n=12$ ). The mean values and standard errors correspond to the output of the Generalized Linear Models, not the raw data itself. **(A)** For *internal noise* estimates, the best fitting model included only the effect of procedure, and so the model output can be seen to vary over the procedures used (deg). **(B)** For *sampling efficiency* estimates the best fitting model included stimulus type, procedure, and the interaction term, therefore the model output contains estimates varying with both stimulus type and procedure. Error bars correspond to 95% confidence interval.

## Discussion

The main aim of the current study was to compare the simplified (2-point) and multisampling (8-point) EN procedures to estimate internal noise and sampling efficiency, for global form, motion, and non-directional motion processing. The 2-point EN paradigm is commonly used with populations that will not necessarily tolerate long experiments, such as children (e.g., Manning et al., 2014; Manning et al., 2022) and clinical populations (e.g., O'Hare et al., 2021; Tibber et al., 2014, 2015), as it is faster and so less demanding in terms of fatigue, etc. The assumptions of the 2-point version are twofold: i) at low levels of directional/orientational variability, the response will be limited by internal noise, and ii) at high levels of directional/orientational variability, the response will be limited by

1  
2  
3  
4 sampling efficiency. However, the shape of the function between these two points is unknown, due to  
5 the sparse sampling. The EN paradigm relies on the assumptions of a linear transducer with additive  
6 noise (Linear Amplifier Model, LAM), which may not be always met, as in the case of contrast  
7 (Baldwin et al., 2016). Commonly, noise is added to RDKs by changing the proportion of signal to  
8 noise dots (e.g., Zanker, 1995). This creates the issue of spurious pairings, known as the  
9 correspondence problem (Dakin et al., 2005). In traditional RDKs, where some dots are signal dots  
10 (moving in a coherent direction) and others are noise dots (moving in random directions), false  
11 correspondences between dots would be a problem for determining the limiting factor of the local  
12 direction estimations (Barlow & Tripathy, 1997). This is partly mitigated in the current experiment  
13 because all dots are signal dots, and so this is analogous to the “zero-dimensional noise” proposed by  
14 Baker et al. (2013) for investigating EN with a contrast masking paradigm. However, it should be noted  
15 that the possibility of spurious matches remains across dot frames, although this can be minimized by  
16 having a relatively large spacing between the dots and moving them by a small amount on each frame  
17 (Williams & Sekuler, 1984). Williams and Sekuler (1984) report that at around 0.1 degrees per second  
18 the likelihood of spurious matches was very low, even at the highest end of the dot densities tested in  
19 their experiment. In the current experiment, the dot density was considerably higher than those tested  
20 by Williams and Sekuler (1984), although the speed is comparable at 0.167 degrees per frame.  
21 Although the correspondence problem has been mitigated to some extent, the possibilities of other non-  
22 linearities cannot be ruled out, therefore it is beneficial to collect data across a range of sampling  
23 points, to assess the shape of the overall function. However, this is not always desirable when working  
24 with certain populations, and so it is important to validate the simplified procedure, as we have done  
25 here. We find good overall agreement when the simplified and multiscale versions are used in the same  
26 observers, showing that the simplified method is valid across a range of different patterns.  
27 The first assumption of the EN paradigm is that under zero-noise conditions the limiting factor of  
28 performance will be the internal noise of the system itself. There are several potential sources of  
29 internal noise for example, photon noise, chromatic aberrations, pupil diffraction, eye movements (for  
30 reviews, see Geisler, 1989; Geisler, 2003). It might be expected that these pre-neural factors would be  
31 relatively stable across stimulus conditions in the current experiment, but the possibility of their effects  
32 cannot be ruled out. Joshi et al. (2021) state that in the case of form and motion perception, one of the  
33 main sources of internal noise could include local signal detection (Joshi et al., 2021), possibly in early  
34 visual cortex (V1/V2). The early visual system contains cells that respond to local orientation (Hubel &

1  
2  
3  
4 Wiesel, 1959) and local motion (Palmer & Davis, 1981). In the static GP, dipoles provide an  
5 orientation signal only, and so local orientation detector noise would be the primary factor contributing  
6 to internal noise. For moving stimuli, local motion detectors are thought to be the first stage of  
7 processing (Heeger et al., 1996), and so this should be the case for the RDKs in the current experiment.  
8 Differently, in the case of dynamic GPs, there is evidence that the visual system uses both local  
9 orientation and motion detectors (Edwards & Crane, 2007; Krekelberg et al., 2003; Johnson &  
10 Wenderoth, 2011; Pavan et al., 2017b). Specifically, for dynamic GPs, the dot lifetime of 100 ms is  
11 sufficient for the motion streak effect to occur (Geisler, 1999). Motion streaks are blurred lines left  
12 behind a rapidly moving object and are an index of form that affect direction judgments (Apthorp et al.,  
13 2009; Geisler, 1999). Geisler (1999) demonstrated that orientation and motion selective neurons in the  
14 early visual cortex V1 are both activated and interact to help the observer to extract form information  
15 that guides motion discrimination decisions. Therefore, in dynamic GPs, local form and motion  
16 detectors can be used together to detect the pattern's ambiguous and illusory direction (Alais et al.,  
17 2010; Edwards & Crane, 2007; Johnson & Wenderoth, 2011; Krekelberg et al., 2003; Pavan et al.,  
18 2017b), therefore noise in both types of detectors contributes to internal noise.

19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
In the case of internal noise estimates, the best fitting model is the one with only the procedure,  
although it must be noted that the effect of procedure was not significant. Despite the 2-point procedure  
tend to overestimate the internal noise parameter compared to the 8-point version, the two methods  
seem to produce similar results. This result is also in line with previous findings (Joshi et al., 2021) and  
suggests that at the local level, motion and orientation detectors are likely to be affected by  
approximatively the same amount of internal noise.

The second assumption of the EN procedure is that at high levels of directional variability the  
response will be limited by sampling efficiency. In the current experiment, we focus on spatial  
sampling efficiency as in previous work (e.g., Joshi et al., 2021), and as this is the most relevant for the  
static GPs. However, it must also be noted that particularly in the case of motion tasks, there are also  
temporal aspects to sampling efficiency (Donato et al., 2021; Watamaniuk et al., 1992; Snowden &  
Braddick, 1991) – for example, human observers average over varying speeds of RDK elements,  
indicating that there are also important temporal integration mechanisms (Watamaniuk & Duchon,  
1992). In a set of experiments investigating efficiency compared to the ideal observer, Watamaniuk  
(1993) demonstrated a 9-frame asymptote for temporal integration for RDKs. In the current  
experiment, although a single dot had a limited lifetime of 5 frames, the overall RDK was displayed for

1  
2  
3  
4 500 ms, which is considerably longer than the time needed for asymptote. Since temporal aspects were  
5 not systematically manipulated in the current study, an investigation in the temporal domain remains  
6 for future research. The best fitting model of our data had variable sampling efficiency estimates for the  
7 different task types, and this showed a similar pattern to Joshi et al. (2021). Specifically, we found that  
8 sampling efficiency for RDKs is higher than for either of the GPs. Sampling efficiency is thought to  
9 relate to the global pooling that is of interest (Dakin et al., 2005), and so this result suggests global  
10 pooling mechanisms are different in global form and motion processing. There is evidence that  
11 confirms this difference, for example Glass and Switkes (1974) observed that black and white dot pairs  
12 in the dipole destroys the overall perception of static GPs, but dot polarity is irrelevant for global  
13 motion detection from RDKs (Edwards & Badcock, 1994). Other studies showed that RDKs are easier  
14 to perceive than dynamic and static GPs (Donato et al., 2020; Nankoo et al., 2012). This distinction  
15 applies not only to simple configurations such as translational patterns but also to more complex  
16 configurations such as radial, circular, and spiral patterns (Donato et al., 2021; Nankoo et al., 2012).  
17 More interestingly, Nankoo et al. (2012) demonstrated not only that RDKs, and GPs are perceived  
18 differently but also that dynamic GPs are processed more similarly to static GPs than RDKs. This  
19 finding could imply that dynamic GPs are processed first for their global form features and only  
20 subsequently for their global motion properties. Our results are in line with this evidence, indicating  
21 that global processing in RDKs and dynamic GPs is mediated by two distinct mechanisms: motion  
22 pooling on the one hand and form-motion integration on the other.

23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36 Although there is relatively good agreement overall, there are also differences in estimates of  
37 sampling efficiency depending on the procedure used. For the 2-point method, estimates of sampling  
38 efficiency are slightly higher for RDKs compared to the 8-point method. Higher sampling efficiency  
39 suggests enhanced pooling of information (Manning et al., 2014; Watamaniuk, 1993). Allard and  
40 Cavanagh (2012) show that greater pooling is a better strategy in more noisy environments.  
41 Improvement in performance (i.e., perceptual learning) for RDKs has been shown merely by exposure  
42 to the motion signal, without participants being aware of their improvement (Watanabe et al., 2001).  
43 Therefore, we hypothesize that participants could have developed better strategies through (implicit)  
44 learning for this class of stimuli. However, how internal noise and sampling efficiency are modulated  
45 by visual perceptual learning and the type of procedure for these classes of stimuli, remains for future  
46 research.  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

1  
2  
3  
4 Direct comparisons of the exact values between the parameter estimates of Joshi et al. (2021)  
5 and the current study may not be possible, due to various reasons, such as slight methodological  
6 differences. For example, slight differences in equipment, and differences in the number of participants  
7 and their level of experience on psychophysical tasks (there were 2/6 vs. 2/12 experienced observers  
8 for Joshi et al. 2021 and the current study, respectively). However, there was a similar overall pattern  
9 of results for the two studies, demonstrating the robustness of the findings.  
10  
11  
12

13 In the current experiment, we used translational GPs, and translational motion for the RDKs.  
14  
15 The choice of translational GPs in the current study was for equivalence with the RDKs. However, it is  
16 worth noting that the spatial summation for this type of GP is thought to be different compared to other  
17 spatial configurations, such as radial and concentric GPs (Wilson & Wilkinson, 1998). Additionally,  
18 there is a difference in how motion signals from translational motion are pooled compared to radial or  
19 circular directions in global motion perception (Freeman & Harris, 1992; Seu & Ferrara, 2001; Lee &  
20 Lu, 2010; Rampone & Makin, 2020), although speed of motion seems to influence this (Lee and Lu,  
21 2010). Wilson and Wilkinson (1998) highlighted that these other configurations are important cues for  
22 other perceptual tasks in the real world, for example, radial motion is related to optic flow patterns that  
23 indicate self-motion and is thought to be pooled over a larger area compared to parallel motion.  
24 Therefore, it is worth investigating these different spatial configurations in future work.  
25  
26  
27  
28  
29  
30  
31

32 In conclusion, we found an overall agreement between the 2-point and the 8-point EN  
33 paradigms in the same set of observers, indicating that the simplified version is a good measure. Our  
34 findings showed a similar pattern of results to Joshi et al. (2021), demonstrating the robustness of the  
35 EN paradigm. Furthermore, they showed that internal noise estimates are similar across stimuli evoking  
36 form, motion, and non-directional motion, indicating that they have a common limiting process,  
37 thought to be local signal detectors in early visual cortex (V1/V2). We also found variability in  
38 sampling efficiency estimates between the three classes of visual stimuli, consistent with Joshi et al.  
39 (2021), indicating that global pooling processes are different for form, motion, and non-directional  
40 motion.  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

## Acknowledgments

This work was carried out within the scope of the project “Use-inspired basic research”, for which the Department of General Psychology of the University of Padova has been recognized as “Dipartimento di Eccellenza” by the Ministry of University and Research. RD was supported by University of Padova, Department of Psychology and by the Human Inspired Centre. This work was also supported in part by the BAGEP Award of the Science Academy - Turkey.

## Data availability statement

All materials (data and code) can be found at <https://osf.io/h6adp/>

## References

- Alais, D., Athorp, D., Karmann, A., & Cass, J. R. (2010). The time-course of motion streak integration at photopic and scotopic light levels. *Perception*, 39(1suppl), 97. Doi: <https://journals.sagepub.com/doi/pdf/10.1177/03010066100390S101>
- Allard, R., & Arleo, A. (2021). The false aperture problem: Global motion perception without integration of local motion signals. *Psychological review*, 10.1037/rev0000347. Advance online publication. <https://doi.org/10.1037/rev0000347>
- Allard, R., & Cavanagh, P. (2012). Different processing strategies underlie voluntary averaging in low and high noise. *Journal of Vision*, 12(11), 6. <https://doi.org/10.1167/12.11.6>
- Anstis, S., & Kim, J. (2011). Local versus global perception of ambiguous motion displays. *Journal of Vision*, 11(3), 13. <https://doi.org/10.1167/11.3.13>
- Athorp, D., Wenderoth, P., & Alais, D. (2009). Motion streaks in fast motion rivalry cause orientation-selective suppression. *Journal of vision*, 9(5), 1–14. <https://doi.org/10.1167/9.5.10>
- Baker, D. H. (2013). What is the primary cause of individual differences in contrast sensitivity? *PloS one*, 8(7), e69536. <https://doi.org/10.1371/journal.pone.0069536>



- 1  
2  
3  
4 Baldwin, A. S., Baker, D. H., & Hess, R. F. (2016). What Do Contrast Threshold Equivalent Noise  
5 Studies Actually Measure? Noise vs. Nonlinearity in Different Masking Paradigms. *PloS one*, *11*(3),  
6 e0150942. <https://doi.org/10.1371/journal.pone.0150942>  
7  
8  
9  
10 Banks, M. S., Sekuler, A. B., & Anderson, S. J. (1991). Peripheral spatial vision: Limits imposed by  
11 optics, photoreceptors, and receptor pooling. *Journal of the Optical Society of America A*, *8*(11), 1775-  
12 1787. [10.1364/josaa.8.001775](https://doi.org/10.1364/josaa.8.001775)  
13  
14  
15  
16  
17 Barlow, H. B. (1957). Increment thresholds at low intensities considered as signal/noise  
18 discriminations. *The Journal of Physiology*, *136*(3), 469. [10.1113/jphysiol.1957.sp005774](https://doi.org/10.1113/jphysiol.1957.sp005774)  
19  
20  
21  
22 Barlow, H., & Tripathy, S. P. (1997). Correspondence noise and signal pooling in the detection of  
23 coherent visual motion. *Journal of Neuroscience*, *17*(20), 7954–7966.  
24  
25 <https://doi.org/10.1523/JNEUROSCI.17-20-07954.1997>  
26  
27  
28  
29 Bates, D., Kliegl, R., Vasishth, S., & Baayen, H. (2015). Parsimonious mixed models. ArXiv Preprint.  
30 Retrieved from <http://arxiv.org/abs/1506.04967>  
31  
32  
33  
34 Beardsley, S. A., & Vaina, L. M. (1998). Computational modelling of optic flow selectivity in MSTd  
35 neurons. *Network*, *9*(4), 467–493. <https://doi.org/10.1088/0954-898X/9/4/005>  
36  
37  
38  
39 Beardsley, S. A., & Vaina, L. M. (2001). A laterally interconnected neural architecture in MST  
40 accounts for psychophysical discrimination of complex motion patterns. *Journal of Computational*  
41 *Neuroscience*, *10*(3), 255–280. <https://doi.org/10.1023/a:1011264014799>  
42  
43  
44  
45  
46 Bogfjellmo, L. G., Bex, P. J., & Falkenberg, H. K. (2013). Reduction in direction discrimination with  
47 age and slow speed is due to both increased internal noise and reduced sampling  
48 efficiency. *Investigative Ophthalmology & Visual Science*, *54*(8), 5204–5210.  
49  
50 <https://doi.org/10.1167/iovs.13-12005>  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

1  
2  
3  
4 Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, 10, 433–436. <https://doi.org/10.1163/156856897X00357>  
5

6  
7  
8 Britten, K. H., Shadlen, M. N., Newsome, W. T., & Movshon, J. A. (1992). The analysis of visual  
9 motion: a comparison of neuronal and psychophysical performance. *Journal of Neuroscience*, 12(12),  
10 4745–4765. <https://doi.org/10.1523/JNEUROSCI.12-12-04745.1992>  
11  
12

13  
14  
15 Cohen, J. (2013). *Statistical power analysis for the behavioral sciences*. Routledge.  
16 <https://doi.org/10.4324/9780203771587>  
17

18  
19  
20 Cropper, S. J. (2001). Local and global motion signals and their interaction in space and time.  
21 In *Motion Vision* (pp. 125-140). Springer, Berlin, Heidelberg. [https://doi.org/10.1007/978-3-642-](https://doi.org/10.1007/978-3-642-56550-2_7)  
22 [56550-2\\_7](https://doi.org/10.1007/978-3-642-56550-2_7)  
23  
24

25  
26  
27 Dakin, S. C. (1997). The detection of structure in glass patterns: Psychophysics and computational  
28 models. *Vision Research*, 37(16), 2227-2246. [https://doi.org/10.1016/S0042-6989\(97\)00038-2](https://doi.org/10.1016/S0042-6989(97)00038-2)  
29  
30

31  
32 Dakin, S. C., Mareschal, I., & Bex, P. J. (2005). Local and global limitations on direction integration  
33 assessed using equivalent noise analysis. *Vision Research*, 45(24), 3027–3049.  
34 <https://doi.org/10.1016/j.visres.2005.07.037>  
35  
36

37  
38  
39 Donato, R., Pavan, A., Almeida, J., Nucci, M., & Campana, G. (2021). Temporal characteristics of  
40 global form perception in translational and circular Glass patterns. *Vision Research*, 187, 102–109.  
41 <https://doi.org/10.1016/j.visres.2021.06.003>  
42  
43

44  
45  
46 Donato, R., Pavan, A., Nucci, M., & Campana, G. (2020). The neural mechanisms underlying  
47 directional and apparent circular motion assessed with repetitive transcranial magnetic stimulation  
48 (rTMS). *Neuropsychologia*, 149, 107656. <https://doi.org/10.1016/j.neuropsychologia.2020.107656>  
49  
50

51  
52  
53 Edwards, M., & Badcock, D. R. (1994). Global motion perception: interaction of the ON and OFF  
54 pathways. *Vision Research*, 34(21), 2849–2858. [https://doi.org/10.1016/0042-6989\(94\)90054-x](https://doi.org/10.1016/0042-6989(94)90054-x)  
55  
56

- 1  
2  
3  
4 Edwards, M., & Crane, M. F. (2007). Motion streaks improve motion detection. *Vision*  
5 *Research*, 47(6), 828–833. <https://doi.org/10.1016/j.visres.2006.12.005>  
6  
7  
8  
9 Falkenberg, H. K., Simpson, W. A., & Dutton, G. N. (2014). Development of sampling efficiency and  
10 internal noise in motion detection and discrimination in school-aged children. *Vision Research*, 100, 8–  
11 17. <https://doi.org/10.1016/j.visres.2014.04.001>  
12  
13  
14  
15 Falkenberg, H. K., Simpson, W. A., & Manahilov, V. (2002). Internal noise and sampling efficiency  
16 for motion detection, discrimination and summation. *Journal of Vision*, 2(7), 645-645.  
17 <https://doi.org/10.1167/2.7.645>  
18  
19  
20  
21  
22  
23 Faul, F., Erdfelder, E., Buchner, A., & Lang, A. G. (2009). Statistical power analyses using G\*Power  
24 3.1: tests for correlation and regression analyses. *Behavior Research Methods*, 41(4), 1149–1160.  
25 <https://doi.org/10.3758/BRM.41.4.1149>  
26  
27  
28  
29  
30 Fox, J. (2003). Effect displays in R for generalised linear models. *Journal of Statistical Software*, 8, 1-  
31 27. <https://doi.org/10.18637/jss.v008.i15>  
32  
33  
34  
35 Freeman, T. C., & Harris, M. G. (1992). Human sensitivity to expanding and rotating motion: effects of  
36 complementary masking and directional structure. *Vision Research*, 32(1), 81-87.  
37 [https://doi.org/10.1016/0042-6989\(92\)90115-Y](https://doi.org/10.1016/0042-6989(92)90115-Y)  
38  
39  
40  
41  
42 Friedman, S. L., & Stevenson, M. B. (1975). Developmental changes in the understanding of implied  
43 motion in two-dimensional pictures. *Child Development*, 46(3), 773–778.  
44 <https://doi.org/10.2307/1128578>  
45  
46  
47  
48  
49 Furlan, M., & Smith, A. T. (2016). Global Motion Processing in Human Visual Cortical Areas V2 and  
50 V3. *Journal of Neuroscience*, 36(27), 7314–7324. <https://doi.org/10.1523/JNEUROSCI.0025-16.2016>  
51  
52  
53  
54 Geisler, W. S. (1989). Sequential ideal-observer analysis of visual discriminations. *Psychological*  
55 *Review*, 96(2), 267. <https://doi.org/10.1037/0033-295X.96.2.267>  
56  
57

- 1  
2  
3  
4 Geisler W. S. (1999). Motion streaks provide a spatial code for motion direction. *Nature*, 400(6739),  
5 65–69. <https://doi.org/10.1038/21886>  
6  
7  
8  
9 Geisler, W.S. (2003). Ideal observer analysis. In Chalupa, Leo M.; Werner, John S. (eds.). *The Visual*  
10 *Neurosciences*. MIT Press. pp. 825–837.  
11  
12  
13  
14 Ghin, F., Pavan, A., Contillo, A., & Mather, G. (2018). The effects of high-frequency transcranial  
15 random noise stimulation (hf-tRNS) on global motion processing: An equivalent noise approach. *Brain*  
16 *Stimulation*, 11(6), 1263–1275. <https://doi.org/10.1016/j.brs.2018.07.048>  
17  
18  
19  
20  
21 Glass L. (1969). Moiré effect from random dots. *Nature*, 223(5206), 578–580.  
22 <https://doi.org/10.1038/223578a0>  
23  
24  
25  
26 Glass, L., & Switkes, E. (1976). Pattern recognition in humans: Correlations which cannot be  
27 perceived. *Perception*, 5(1), 67-72. <https://doi.org/10.1068/p050067>  
28  
29  
30  
31 Grossman, E. D., & Blake, R. (1999). Perception of coherent motion, biological motion and form-from-  
32 motion under dim-light conditions. *Vision Research*, 39(22), 3721–3727.  
33 [https://doi.org/10.1016/s0042-6989\(99\)00084-x](https://doi.org/10.1016/s0042-6989(99)00084-x)  
34  
35  
36  
37  
38 Heeger, D. J., Simoncelli, E. P., & Movshon, J. A. (1996). Computational models of cortical visual  
39 processing. *Proceedings of the National Academy of Sciences*, 93(2), 623-627.  
40 <https://www.pnas.org/doi/epdf/10.1073/pnas.93.2.623>  
41  
42  
43  
44  
45 Hoffman, J. E. (1980). Interaction between global and local levels of a form. *Journal of Experimental*  
46 *Psychology: Human Perception and Performance*, 6(2), 222–234. [https://doi.org/10.1037//0096-](https://doi.org/10.1037//0096-1523.6.2.222)  
47 [1523.6.2.222](https://doi.org/10.1037//0096-1523.6.2.222)  
48  
49  
50  
51  
52 Hubel, D. H., & Wiesel, T. N. (1959). Receptive fields of single neurones in the cat's striate cortex. *The*  
53 *Journal of Physiology*, 148(3), 574–591. <https://doi.org/10.1113/jphysiol.1959.sp006308>  
54  
55  
56  
57  
58  
59  
60

- 1  
2  
3  
4 Johnson, B., & Wenderoth, P. (2011). Tapered dipoles in briefly flashed glass-pattern sequences  
5 disambiguate perceived motion direction. *Perception*, *40*(4), 383–391. <https://doi.org/10.1068/p6813>  
6  
7  
8  
9 Joshi, M. R., Simmers, A. J., & Jeon, S. T. (2016). Concurrent Investigation of Global Motion and  
10 Form Processing in Amblyopia: An Equivalent Noise Approach. *Investigative Ophthalmology & Visual*  
11 *Science*, *57*(11), 5015–5022. <https://doi.org/10.1167/iovs.15-18609>  
12  
13  
14  
15  
16 Joshi, M. R., Simmers, A. J., & Jeon, S. T. (2020). Implied motion from form shows motion aids the  
17 perception of global form in amblyopia. *Investigative Ophthalmology & Visual Science*, *61*(5), 58.  
18 <https://doi.org/10.1167/iovs.61.5.58>  
19  
20  
21  
22  
23 Joshi, M. R., Simmers, A. J., & Jeon, S. T. (2021). The interaction of global motion and global form  
24 processing on the perception of implied motion: An equivalent noise approach. *Vision Research*, *186*,  
25 34–40. <https://doi.org/10.1016/j.visres.2021.04.006>  
26  
27  
28  
29  
30 Kleiner, M., Brainard, D.H., Pelli, D.G., Broussard, C., Wolf, T., Niehorster, D., 2007. What’s new in  
31 Psychtoolbox-3? *Perception*. <https://doi.org/10.1068/v070821>.  
32  
33  
34  
35 Krekelberg, B., Dannenberg, S., Hoffmann, K. P., Bremmer, F., & Ross, J. (2003). Neural correlates of  
36 implied motion. *Nature*, *424*(6949), 674–677. <https://doi.org/10.1038/nature01852>  
37  
38  
39  
40 Krekelberg, B., Vatakis, A., & Kourtzi, Z. (2005). Implied motion from form in the human visual  
41 cortex. *Journal of Neurophysiology*, *94*(6), 4373–4386. <https://doi.org/10.1152/jn.00690.2005>  
42  
43  
44  
45 Lee, A. L., & Lu, H. (2010). A comparison of global motion perception using a multiple-aperture  
46 stimulus. *Journal of Vision*, *10*(4), 1–16. <https://doi.org/10.1167/10.4.9>  
47  
48  
49  
50 Levitt, H. (1971). Transformed up-down methods in psychoacoustics. *The Journal of the Acoustical*  
51 *Society of America*, *49*(2), 467-477. <https://doi.org/10.1121/1.1912375>  
52  
53  
54  
55  
56  
57  
58  
59  
60

1  
2  
3  
4 Leys, C., Ley, C., Klein, O., Bernard, P., & Licata, L. (2013). Detecting outliers: Do not use standard  
5 deviation around the mean, use absolute deviation around the median. *Journal of Experimental Social*  
6 *Psychology*, 49(4), 764-766. <https://doi.org/10.1016/j.jesp.2013.03.013>  
7  
8

9  
10 Loffler, G., Wilson, H. R., & Wilkinson, F. (2003). Local and global contributions to shape  
11 discrimination. *Vision Research*, 43(5), 519–530. [https://doi.org/10.1016/s0042-6989\(02\)00686-7](https://doi.org/10.1016/s0042-6989(02)00686-7)  
12  
13

14  
15  
16 Lorteije, J. A., Kenemans, J. L., Jellema, T., van der Lubbe, R. H., de Heer, F., & van Wezel, R. J.  
17 (2006). Delayed response to animate implied motion in human motion processing areas. *Journal of*  
18 *Cognitive Neuroscience*, 18(2), 158–168. <https://doi.org/10.1162/089892906775783732>  
19  
20

21  
22  
23 Manning, C., Dakin, S. C., Tibber, M. S., & Pellicano, E. (2014). Averaging, not internal noise, limits  
24 the development of coherent motion processing. *Developmental Cognitive Neuroscience*, 10, 44-56.  
25 <https://doi.org/10.1016/j.dcn.2014.07.004>  
26  
27

28  
29  
30 Manning, C., Hulks, V., Tibber, M. S., & Dakin, S. C. (2022). Integration of visual motion and  
31 orientation signals in dyslexic children: an equivalent noise approach. *Royal Society Open Science*,  
32 9(5), 200414. <https://doi.org/10.1098/rsos.200414>  
33  
34

35  
36  
37 Manning, C., Tibber, M. S., Charman, T., Dakin, S. C., & Pellicano, E. (2015). Enhanced integration of  
38 motion information in children with autism. *Journal of Neuroscience*, 35(18), 6979–6986.  
39 <https://doi.org/10.1523/JNEUROSCI.4645-14.2015>  
40  
41

42  
43  
44 Manning, C., Tibber, M. S., & Dakin, S. C. (2017). Visual integration of direction and orientation  
45 information in autistic children. *Autism & Developmental Language Impairments*, 2,  
46 2396941517694626.  
47  
48

49  
50  
51 McKendrick, A. M., Badcock, D. R., & Morgan, W. H. (2005). The detection of both global motion  
52 and global form is disrupted in glaucoma. *Investigative Ophthalmology & Visual Science*, 46(10),  
53 3693–3701. <https://doi.org/10.1167/iovs.04-1406>  
54  
55  
56  
57

1  
2  
3  
4 Morrone, M. C., Burr, D. C., & Vaina, L. M. (1995). Two stages of visual processing for radial and  
5 circular motion. *Nature*, 376(6540), 507-509. <https://www.nature.com/articles/376507a0>

6  
7  
8  
9 Nankoo, J. F., Madan, C. R., Spetch, M. L., & Wylie, D. R. (2012). Perception of dynamic glass  
10 patterns. *Vision Research*, 72, 55–62. <https://doi.org/10.1016/j.visres.2012.09.008>

11  
12  
13  
14 O'Hare, L., Goodwin, P., Sharp, A., Contillo, A., & Pavan, A. (2021). Improvement in visual  
15 perception after high-frequency transcranial random noise stimulation (hf-tRNS) in those with  
16 migraine: An equivalent noise approach. *Neuropsychologia*, 161, 107990.  
17  
18 <https://doi.org/10.1016/j.neuropsychologia.2021.107990>

19  
20  
21  
22 Palmer, L. A., & Davis, T. L. (1981). Comparison of responses to moving and stationary stimuli in cat  
23 striate cortex. *Journal of Neurophysiology*, 46(2), 277-295. <https://doi.org/10.1152/jn.1981.46.2.277>

24  
25  
26  
27  
28 Pavan, A., Contillo, A., Ghin, F., Donato, R., Foxwell, M. J., Atkins, D. W., Mather, G., & Campana,  
29 G. (2021). Spatial and temporal selectivity of translational Glass patterns assessed with the tilt after-  
30 effect. *i-Perception*, 12(3), 20416695211017924. <https://doi.org/10.1177/20416695211017924>

31  
32  
33  
34  
35 Pavan, A., Ghin, F., Contillo, A., Milesi, C., Campana, G., & Mather, G. (2019). Modulatory  
36 mechanisms underlying high-frequency transcranial random noise stimulation (hf-tRNS): A combined  
37 stochastic resonance and equivalent noise approach. *Brain Stimulation*, 12(4), 967–977.  
38  
39 <https://doi.org/10.1016/j.brs.2019.02.018>

40  
41  
42  
43 Pavan, A., Bimson, L. M., Gall, M. G., Ghin, F., & Mather, G. (2017a). The interaction between  
44 orientation and motion signals in moving oriented Glass patterns. *Visual Neuroscience*, 34, E010.  
45  
46 <https://doi.org/10.1017/S0952523817000086>

47  
48  
49  
50 Pavan, A., Ghin, F., Donato, R., Campana, G., & Mather, G. (2017b). The neural basis of form and  
51 form-motion integration from static and dynamic translational Glass patterns: A rTMS  
52 investigation. *NeuroImage*, 157, 555–560. <https://doi.org/10.1016/j.neuroimage.2017.06.036>  
53  
54  
55  
56  
57

1  
2  
3  
4 Pavan, A., Cuturi, L. F., Maniglia, M., Casco, C., & Campana, G. (2011). Implied motion from static  
5 photographs influences the perceived position of stationary objects. *Vision Research*, *51*(1), 187–194.  
6 <https://doi.org/10.1016/j.visres.2010.11.004>  
7  
8

9  
10 Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into  
11 movies. *Spatial Vision*, *10*, 437–442. <https://doi.org/10.1163/156856897X00366>.  
12  
13

14  
15 Pelli, D. G., & Farell, B. (1999). Why use noise? *Journal of the Optical Society of America A*, *16*(3),  
16 647–653. <https://doi.org/10.1364/josaa.16.000647>  
17  
18

19  
20 R Core Team (2022). R: A language and environment for statistical computing. R Foundation for  
21 Statistical Computing, Vienna, Austria. URL <https://www.R-project.org/>.  
22  
23

24  
25 Rampone, G., & Makin, A. (2020). Electrophysiological responses to regularity show specificity to  
26 global form: The case of Glass patterns. *The European Journal of Neuroscience*, *52*(3), 3032–3046.  
27 <https://doi.org/10.1111/ejn.14709>  
28  
29

30  
31 Rajananda, S., Lau, H., & Odegaard, B. (2018). A random-dot kinematogram for web-based vision  
32 research. *Journal of Open Research Software*, *6*(1). <https://doi.org/10.5334/jors.194>  
33  
34

35  
36 Ross, J., Badcock, D. R., & Hayes, A. (2000). Coherent global motion in the absence of coherent  
37 velocity signals. *Current Biology*, *10*, 679–682. [https://doi.org/10.1016/S0960-9822\(00\)00524-8](https://doi.org/10.1016/S0960-9822(00)00524-8)  
38  
39

40  
41 Seu, L., & Ferrera, V. P. (2001). Detection thresholds for spiral Glass patterns. *Vision*  
42 *Research*, *41*(28), 3785–3790. [https://doi.org/10.1016/s0042-6989\(01\)00235-8](https://doi.org/10.1016/s0042-6989(01)00235-8)  
43  
44

45  
46 Simpson, W. A., Falkenberg, H. K., & Manahilov, V. (2003). Sampling efficiency and internal noise  
47 for motion detection, discrimination, and summation. *Vision Research*, *43*(20), 2125–2132.  
48  
49  
50 [https://doi.org/10.1016/S0042-6989\(03\)00336-5](https://doi.org/10.1016/S0042-6989(03)00336-5)  
51  
52  
53  
54  
55  
56  
57



1  
2  
3  
4 Snowden, R. J., & Braddick, O. J. (1991). The temporal integration and resolution of velocity  
5 signals. *Vision research*, 31(5), 907–914. [https://doi.org/10.1016/0042-6989\(91\)90156-y](https://doi.org/10.1016/0042-6989(91)90156-y)  
6  
7

8  
9 Snowden, R. J., & Kavanagh, E. (2006). Motion perception in the ageing visual system: minimum  
10 motion, motion coherence, and speed discrimination thresholds. *Perception*, 35(1), 9–24.  
11 <https://doi.org/10.1068/p5399>  
12  
13

14  
15  
16 Tibber, M. S., Kelly, M. G., Jansari, A., Dakin, S. C., & Shepherd, A. J. (2014). An inability to exclude  
17 visual noise in migraine. *Investigative Ophthalmology and Visual Science*, 55(4), 2539–2546.  
18 <https://doi.org/10.1167/iovs.14-13877>  
19  
20

21  
22  
23 Tibber, M. S., Anderson, E. J., Bobin, T., Carlin, P., Shergill, S. S., & Dakin, S. C. (2015). Local and  
24 global limits on visual processing in schizophrenia. *PLoS One*, 10(2), e0117951.  
25 <https://doi.org/10.1371/journal.pone.0117951>  
26  
27

28  
29 Theraja, B. L., & Theraja, A. K. (2005). A textbook of electrical technology, New Delhi: S. Chand &  
30 *Company Ltd.*  
31  
32

33  
34  
35 Watamaniuk, S. N. (1993). Ideal observer for discrimination of the global direction of dynamic  
36 random-dot stimuli. *Journal of the Optical Society of America. A*, 10(1), 16–28.  
37 <https://doi.org/10.1364/josaa.10.000016>  
38  
39

40  
41  
42 Watamaniuk, S. N., & Duchon, A. (1992). The human visual system averages speed information.  
43 *Vision Research*, 32(5), 931-941. [https://doi.org/10.1016/0042-6989\(92\)90036-I](https://doi.org/10.1016/0042-6989(92)90036-I)  
44  
45

46  
47  
48 Watamaniuk, S. N., & Heinen, S. J. (1999). Human smooth pursuit direction discrimination. *Vision*  
49 *Research*, 39, 59–70. [https://doi.org/10.1016/S0042-6989\(98\)00128-X](https://doi.org/10.1016/S0042-6989(98)00128-X)  
50  
51

52  
53  
54 Watamaniuk, S. N., & Sekuler, R. (1992). Temporal and spatial integration in dynamic random-dot  
55 stimuli. *Vision Research*, 32(12), 2341–2347. [https://doi.org/10.1016/0042-6989\(92\)90097-3](https://doi.org/10.1016/0042-6989(92)90097-3)  
56  
57

1  
2  
3  
4 Watamaniuk, S.N.J., Sekuler, R., & McKee, S.P. (2011). Perceived global flow direction reveals local  
5 vector weighting by luminance. *Vision Research*, 51, 1129-1136.

6  
7 <https://doi.org/10.1016/j.visres.2011.03.003>  
8  
9

10 Watamaniuk, S.N.J., Sekuler, R. & Williams, D.W. (1989). Direction perception in complex dynamic  
11 displays: the integration of direction information. *Vision Research*, 29, 47-59.

12  
13 [https://doi.org/10.1016/0042-6989\(89\)90173-9](https://doi.org/10.1016/0042-6989(89)90173-9)  
14  
15

16  
17 Watanabe, T., Nanez, J. E., & Sasaki, Y. (2001). Perceptual learning without perception. *Nature*,  
18 413(6858), 844-848. <https://www.nature.com/articles/35101601>  
19  
20

21  
22 Watt, R. J., & Morgan, M. J. (1984). Spatial filters and the localization of luminance changes in human  
23 vision. *Vision Research*, 24(10), 1387-1397. [https://doi.org/10.1016/0042-6989\(84\)90194-9](https://doi.org/10.1016/0042-6989(84)90194-9)  
24  
25

26  
27 Wetherill, G. B., & Levitt, H. (1965). Sequential estimation of points on a psychometric function. *The*  
28 *British Journal of Mathematical and Statistical Psychology*, 18, 1–10. [https://doi.org/10.1111/j.2044-](https://doi.org/10.1111/j.2044-8317.1965.tb00689.x)  
29 [8317.1965.tb00689.x](https://doi.org/10.1111/j.2044-8317.1965.tb00689.x)  
30  
31

32  
33 Williams, D. W., & Sekuler, R. (1984). Coherent global motion percepts from stochastic local motions.  
34 *Vision Research*, 24, 55–62. <https://doi.org/10.1145/988525.988533>  
35  
36

37  
38 Wilson, H. R., & Wilkinson, F. (1998). Detection of global structure in Glass patterns: Implications for  
39 form vision. *Vision Research*, 38(19), 2933-2947. [https://doi.org/10.1016/S0042-6989\(98\)00109-6](https://doi.org/10.1016/S0042-6989(98)00109-6)  
40  
41  
42

43  
44 World Medical Association. (2013). World Medical Association Declaration of Helsinki ethical  
45 principles for medical research involving human subjects. *JAMA: Journal of the American Medical*  
46 *Association*, 310(20), 2191–2194.  
47  
48  
49

50  
51 Yamamoto, K., & Miura, K. (2012). Time dilation caused by static images with implied motion.  
52 *Experimental Brain Research*, 223(2), 311–319. <https://doi.org/10.1007/s00221-012-3259-5>  
53  
54  
55

1  
2  
3  
4 Zanker, J. M. (1995). Does motion perception follow Weber's law? *Perception*, 24(4), 363-372.  
5 <https://doi.org/10.1068/p240363>  
6  
7

8  
9 Zuur, A. F., Ieno, E. N., & Elphick, C. S. (2010). A protocol for data exploration to avoid common  
10 statistical problems. *Methods in Ecology and Evolution*, 1(1), 3-14.  
11 <https://doi.org/10.1111/j.2041-210X.2009.00001.x>  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60